



THIS IS A C.A.D. GENERATED DRAWING
DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER
ORIGINAL ①

ELECTRICAL:

CONTACT CURRENT: 1 AMP
 DIELECTRIC WITHSTANDING VOLTAGE: 750 VAC R.M.S.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.

MATERIALS:

SHELL: COPPER ALLOY, TIN-LEAD PLATED
 CONTACTS: COPPER ALLOY GOLD PLATE ON CONTACT AREA
 TIN-LEAD ON TAIL END
 GOLD FLASH 261 CONTACT CODE
 15 MICROINCHES OF GOLD 361 CONTACT CODE
 30 MICROINCHES OF GOLD 661 CONTACT CODE
 INSULATOR: THERMOPLASTIC (HIGH TEMPERATURE RESISTANCE)

PART NUMBER: 690-004-261-013

CONTACT CODE _____

USB CONNECTOR "A" TYPE, RECEPTACLE RIGHT ANGLE VERTICAL		ACAD REFERENCE NO. 690-004-261-013	
		DRAWN: F.BRIONES	DATE: JAN.22/04
EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE		CHECKED:	DATE:
		SCALE: (IN C.A.D. 1:1) SHEET 1 OF 1	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.		DRAWING NUMBER	ISSUE
		690-004-261-013	1