



Notes:

- Electrical Specifications:
 - Meets USB 2.0 Specification
 - Contact Resistance: 30 mOhm max.
 - Insulation Resistance: 1000 MOhm min. @ 100 VDC
 - Current Rating: 1.5 A max. at 25°C
 - Working Voltage: 30 V (RMS) max.
 - DWV: 500 VAC/60s at sea Level
 - Operating Temperature: -40°C to +85°C
- Material and Finish:
 - Metal Coupling Ring: Brass, Nickel Plated
 - Plug Housing: ABS, Nickel Plated, UL94 V-0
 - Interfacial Seal: Silicone, Color: White
 - Cable Fitting: PA (Black), UL94 V-0
 - Cable Fitting Rubber Ring: NBR, Color: Black
 - USB Metal Shell: SPCC, Nickel Plated
 - USB Insulator: PBT UL94 V-0
 - USB Contacts: Copper Alloy
 - USB Contact Finish: 30 u" Gold min. over Nickel for mating area, Tin over Nickel for solder cup
- USB Type A Plug accepts AWG28 to AWG24 wires. Cable with outer Diameter of 4.06 mm to 5.21mm
- Cable Fitting accepts Cable Outer Diameter Range of 4 mm to 8 mm
- RoHS compliant

Directive 2002/95/EC
"RoHS"
Compliant

THIS DRAWING AND THESE DIMENSIONS ARE PRELIMINARY IN ANY WAY AND MAY NOT BE PASSED ON TO THIRD PARTIES WITHOUT THE EXPRESS WRITTEN PERMISSION OF CONEC CORPORATION DO NOT ALTER CAD DRAWING BY HAND	Customer:		Tolerance Unless otherwise specified			Scale: 1.5:1	Dim. in mm	
	Name	Title	Approval Date	0 PLC ±0.10 1 PLC ±0.38 2 PLC ±0.51 3 PLC ±0.10 ANGLES ±3°		Autodesk Inventor	Material: See Notes	
				2008	Date	Name	Title: IP67 USB 2.0	
				Draw.	Oct 31	Vincent Ke	Type A Plug (Solder Cup) Assembly Kit	
				Appd.	Oct 31	J. Chaudry	Metal Version	
			Norm			Drawing No.: 17K1A115		
			D-old			Part No.: 17-200331		
	a	original			CONEC		DIN A3	
Rev.	Changes	Date	Name				Sheet 1/1	