



**Notes:**

1. Electrical Specifications:
  - Meets USB 2.0 Specification
  - Contact Resistance: 30 mOhm max.
  - Insulation Resistance: 1000 MOhm min. @ 100 VDC
  - Current Rating: 1.5 A max. at 25° C
  - Working Voltage: 30 V (RMS) max.
  - DWV: 500 VAC/60s at sea Level
  - Operating Temperature: -40° C to +85° C
2. Material and Finish:
  - Coupling Ring and Plug Housing: Polyester (Black), UL94 V-0
  - Interfacial Seal: Silicone, Color: White
  - Cable Fitting: PA (Black), UL94 V-0
  - Cable Fitting Rubber Ring: NBR, Color: Black
  - USB Metal Shell: SPCC, Nickel Plated
  - USB Insulator: PBT, UL94 V-0, White
  - USB Contacts: Copper Alloy,
  - USB Contact Finish: 30 u" Gold min. over Nickel for mating area, Tin over Nickel for solder cup
3. USB Type A Plug accepts AWG28 to AWG24 wires, Cable with outer Diameter of 4.06 mm to 5.21 mm
4. Cable Fitting accepts Cable Outer Diameter Range of 4 mm to 8 mm
5. RoHS compliant

Directive 2002/95/EC  
"RoHS"  
Compliant

THIS DRAWING AND THESE DIMENSIONS ARE THE PROPERTY OF CONEC INC. IN ANY MANNER AND MAY NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE EXPRESS WRITTEN PERMISSION OF CONEC INC.	Customer:			Tolerance Unless otherwise specified		 Autodesk Inventor	Scale: 1.5:1	Dim. in mm						
	Name	Title	Approval Date	0 1 2 3	PLC PLC PLC PLC		±0.10 ±0.38 ±0.51 ±0.10	ANGLES ±3°	Material: See Notes					
	2008	Date	Name						Title: IP67 USB					
	Draw.	Sept. 09	Vincent Ke						USB Cable Strain Relief Assembly Kit with Solder Cup USB 2.0 Type A plug					DIN A3
	Appd.	Sept. 09	J. Chaudry											Drawing No.: 17K1A009
Norm	D-old		Part No.: 17-200151											
a	original							Rev. Changes Date Name						