



- Notes:**
- Electrical Specifications:
 - Meets USB 2.0 Specification
 - Contact Resistance: 30 mOhm max.
 - Insulation Resistance: 1000 MOhm min. @ 100 VDC
 - Current Rating: 1.5 A max. at 25° C
 - Working Voltage: 30 V (RMS) max.
 - DWV: 500 VAC/60s at sea Level
 - Operating Temperature: -40° C to +85° C
 - Material and Finish:
 - Coupling Ring: Zinc Die-Cast, Nickel Plated
 - USB Plug Housing: ABS, UL94 V-0, Nickel Plated
 - Interfacial Seal: Silicone, Color: White
 - Cable Fitting: Brass, Nickel Plated
 - Cable Fitting Rubber Ring: NBR, Color: Black
 - USB Metal Shell: SPCC, Nickel Plated
 - USB Insulator: PBT, UL94 V-0, White
 - USB Contacts: Copper Alloy,
 - USB Contact Finish: 30 u" Gold min. over Nickel for mating area, Tin over Nickel for solder cup
 - USB Type A Plug accepts AWG28 to AWG24 wires, Cable with outer Diameter of 4.06 mm to 5.21 mm
 - Cable Fitting accepts Cable Outer Diameter Range of 4 mm to 8 mm
 - RoHS compliant
 - IP67 rated when fully mated with appropriate mating connector

Directive 2002/95/EC
"RoHS"
Compliant

THIS DRAWING AND THE CONTENTS THEREOF ARE UNCLASSIFIED IN ANY WAY AND MAY NOT BE RECLASSIFIED TO A THIRD PARTY WITHOUT THE WRITTEN PERMISSION OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified			Scale: 1.5:1	Dim. in mm
	Name	Title	Approval Date	0 1 2 3	PLC PLC PLC PLC		Autodesk Inventor	Material: See Notes
				2010	Date	Name	Title: Die-Cast IP67 USB Plug Kit with USB 2.0 Type A Plug Solder Cup Version	
				Draw.	Mar. 16	Vincent Ke		
				Appd.	Mar. 16	J. Chaudry		
				Norm			Drawing No.: 17K1A154	DIN A3
				D-old			Part No.: 17-200591	Sheet 1/1

