


**Product Details for 2 -406372 -2**



**2-406372 -2**

Active

**Cable Mounted Jacks**

[5 of 6 RoHS/ELV Compliant](#) (Statement of Compliance)

**Product Highlights:**

- ? Jack
- ? Jack Type = 110Connect
- ? Number of Positions = 8
- ? Wiring Pattern = Universal
- ? Termination Style = 110 style punch down

[View all Features](#)

**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- ? [110 MODULAR JACK ASSEMBLY, RJ45, ENHANCED CAT5, UNIV...](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- ? None Available

**Product Specifications:**

- ? None Available

**Application Specifications:**

- ? None Available

**Instruction Sheets:**

- ? [Unshielded 110Connect Panel Mount Jacks \(Category 3 ...](#) (PDF, English)

**CAD Files:** ([CAD Format & Compression Information](#))

- ? [3D Model](#) (STEP, Version D)
- ? [3D Model](#) (IGES, Version D)
- ? [2D Drawing](#) (DXF, Version D)

[List all Documents](#)

**Additional Information:**

- ? [Product Line Information](#)

**Additional Product Images:**

- ? [Product Photo](#)

**Related Products:**

- ? [Tooling](#)

**Product Features**

(Please use the Product Drawing for all design activity)

**Product Type Features:**

- ? Product Type = Jack
- ? [Jack Type](#) = 110Connect
- ? Number of Positions = 8
- ? Wiring Pattern = Universal
- ? [Termination Style](#) = 110 style punch -down
- ? [Keyed](#) = No
- ? Shielded = No
- ? [Performance Category](#) = Enhanced Cat 5
- ? Comment = T568A and T568B wiring patterns combined in one P/N.

**Body Related Features:**

- ? NETCONNECT Select System = No
- ? Mount Type = Panel Mount
- ? Wire Range (Solid) (mm [AWG]) = 22 -26
- ? Wire Range (Stranded) (mm [AWG]) = 20 -26
- ? 110 Block Material = Polycarbonate

**Contact Related Features:**

- ? Contact Material = Phosphor Bronze
- ? Contact Mating Area Plating = Gold (50) over Nickel
- ? Contact Termination Area Plating = Tin Lead over Nickel

**Housing Related Features:**

- ? Housing Color = Black
- ? Housing Material = Polyphenylene Oxide
- ? Housing Flammability Rating = UL 94V -0

**Industry Standards:**

- ? [RoHS/ELV Compliance](#) = ELV compliant, 5 of 6 Compliant
- ? [Lead Free Solder Processes](#) = Not relevant for lead free process

**Packaging Related Features:**

- ? Packaging Method = Poly Bag
- ? Packaging Quantity = 25

**Other:**

- ? Brand = AMP