


Metallized Polyester Film Capacitors

Related Document: IEC 60384-2

Dimensions in millimeters



MAIN APPLICATIONS

Blocking, bypassing, filtering and timing, high frequency coupling and decoupling. Interference suppression in low voltage applications.

MARKING

Manufacturer's logo/type/C-value/rated voltage/tolerance/date of manufacture

DIELECTRIC

Polyester film

ELECTRODES

Vacuum deposited aluminum

COATING

Flame retardant plastic case (UL-class 94 V-0), epoxy resin sealed

CONSTRUCTION

Extended metallized film (refer to general information)

LEADS

Tinned wire

IEC TEST CLASSIFICATION

55/100/56, according to IEC 60068

OPERATING TEMPERATURE RANGE

- 55 °C to + 100 °C

CAPACITANCE RANGE

1000 pF to 1.0 µF

CAPACITANCE TOLERANCES

± 20 % (M), ± 10 % (K), ± 5 % (J)

RATED VOLTAGES (U_R)

63 V_{DC}, 100 V_{DC}, 250 V_{DC}, 400 V_{DC}, 630 V_{DC}

FEATURES

- Compliant to RoHS directive 2002/95/EC

PERMISSIBLE AC VOLTAGES (RMS) UP TO 60 Hz

40 V_{AC}, 63 V_{AC}, 160 V_{AC}, 200 V_{AC}, 220 V_{AC}

TEST VOLTAGE (ELECTRODE/ELECTRODE)

1.6 x U_R for 2 s

INSULATION RESISTANCE

Measured with 100 V_{DC} (63 V_{DC} series at 50 V_{DC}) after one minute

For C ≤ 0.33 µF and U_R > 100 V_{DC}:

30 000 MΩ minimum value (100,000 MΩ typical value)

For C ≤ 0.33 µF and U_R ≤ 100 V_{DC}:

15 000 MΩ minimum value (50 000 MΩ typical value)

TIME CONSTANT

Measured at 100 V_{DC} (63 V_{DC} series measured at 50 V_{DC}) after one minute

For C > 0.33 µF and U_R ≤ 100 V_{DC}:

5000 s minimum value (15 000 s typical value)

CAPACITANCE DRIFT

Up to + 40 °C, ± 1.5 % for a period of two years

DERATING FOR DC AND AC. CATEGORY VOLTAGE U_C

At + 85 °C: U_C = 1.0 U_R

At + 100 °C: U_C = 0.8 U_R

SELF INDUCTANCE

~ 6 nH measured with 2 mm long leads

PULL TEST ON LEADS

≥ 30 N in direction of leads according to IEC 60068-2-21

RELIABILITY

Operational life > 300 000 Hz

Failure rate < 2 FIT (40 °C and 0.5 x U_R)



RoHS
COMPLIANT

For further details, please refer to the general information available at www.vishay.com/doc?26033.

MAXIMUM PULSE RISE TIME

PCM (mm)	Maximum Pulse Rise Time dV/dt [V/μs]				
	63 V _{DC}	100 V _{DC}	250 V _{DC}	400 V _{DC}	630 V _{DC}
7.5	12	20	32	41	70

Note

If the maximum pulse voltage is less than the rated voltage higher dV/dt values can be permitted.

DISSIPATION FACTOR TAN δ

MEASURED AT	C ≤ 0.1 μF	0.1 μF < C ≤ 1.0 μF
1 kHz	8 x 10 ⁻³	8 x 10 ⁻³
10 kHz	15 x 10 ⁻³	15 x 10 ⁻³
100 kHz	25 x 10 ⁻³	-
Maximum values		

CAPACITANCE	CAPACITANCE CODE	VOLTAGE CODE 06 63 V _{DC} /40 V _{AC}			VOLTAGE CODE 01 100 V _{DC} /63 V _{AC}			VOLTAGE CODE 25 250 V _{DC} /160 V _{AC}			VOLTAGE CODE 40 400 V _{DC} /200 V _{AC}			VOLTAGE CODE 63 ⁽¹⁾ 630 V _{DC} /220 V _{AC}		
		W	H	L	W	H	L	W	H	L	W	H	L	W	H	L
		1000 pF	-210	-	-	-	-	-	-	-	-	-	-	-	-	2.5
1500 pF	-215	-	-	-	-	-	-	-	-	-	-	-	-	2.5	7.5	10.0
2200 pF	-222	-	-	-	-	-	-	-	-	-	-	-	-	2.5	7.5	10.0
3300 pF	-233	-	-	-	-	-	-	-	-	-	2.5	7.5	10.0	3.0	8.5	10.0
4700 pF	-247	-	-	-	-	-	-	-	-	-	2.5	7.5	10.0	-	-	-
6800 pF	-268	-	-	-	-	-	-	-	-	-	2.5	7.5	10.0	-	-	-
0.01 μF	-310	-	-	-	-	-	-	2.5	7.5	10.0	3.0	8.5	10.0	-	-	-
0.015 μF	-315	-	-	-	-	-	-	2.5	7.5	10.0	-	-	-	-	-	-
0.022 μF	-322	-	-	-	2.5	7.5	10.0	3.0	8.5	10.0	-	-	-	-	-	-
0.033 μF	-333	-	-	-	2.5	7.5	10.0	3.0	8.5	10.0	-	-	-	-	-	-
0.047 μF	-347	-	-	-	2.5	7.5	10.0	4.0	9.0	10.0	-	-	-	-	-	-
0.068 μF	-368	-	-	-	2.5	7.5	10.0	4.5	9.5	10.0	-	-	-	-	-	-
0.1 μF	-410	2.5	7.5	10.0	3.0	8.5	10.0	5.0	10.5	10.3	-	-	-	-	-	-
0.15 μF	-415	2.5	7.5	10.0	3.0	8.5	10.0	-	-	-	-	-	-	-	-	-
0.22 μF	-422	3.0	8.5	10.0	4.0	9.0	10.0	-	-	-	-	-	-	-	-	-
0.33 μF	-433	4.0	9.0	10.0	5.0	10.5	10.3	-	-	-	-	-	-	-	-	-
0.47 μF	-447	4.5	9.5	10.0	5.7	11.5	10.3	-	-	-	-	-	-	-	-	-
0.68 μF	-468	5.0	10.5	10.3	-	-	-	-	-	-	-	-	-	-	-	-
1.0 μF	-510	5.7	11.5	10.3	-	-	-	-	-	-	-	-	-	-	-	-

Notes

- Further values upon request

⁽¹⁾ Not suitable for mains applications.


Please refer to X-capacitors in our catalog "RFI Suppression Components".

RECOMMENDED PACKAGING


LETTER CODE	TYPE OF PACKAGING	HEIGHT (H) (mm)	REEL DIAMETER (mm)	ORDERING CODE EXAMPLE	PCM 7.5
D	Ammo	16.5	S ⁽¹⁾	MKT 1818-310-255-D	X
G	Ammo	18.5	S ⁽¹⁾	MKT 1818-310-255-G	X
F	Reel	16.5	350	MKT 1818-310-255-F	X
W	Reel	18.5	350	MKT 1818-310-255-W	X
-	Bulk	-	-	MKT 1818-310-255	X

Note


⁽¹⁾ S = box size 55 mm x 210 mm x 340 mm (W x H x L)




Permissible AC Voltage versus Frequency




Permissible AC Voltage versus Frequency



Permissible AC Voltage versus Frequency



Permissible AC Voltage versus Frequency



Permissible AC Voltage versus Frequency



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.