


## Interference Suppression Film Capacitors MKP Radial Potted Type



**NO FOCUS PRODUCT: USE MKP 339 X2**

### APPLICATIONS

X2 class

For X2 electromagnetic interference suppression in across the line applications (50/60 Hz) with a maximum mains voltage of 275 VAC.

For application limitations please refer page 5.

### REFERENCE STANDARDS

"IEC 60384-14 2nd edition and EN 132400"

"IEC 60065, pass. flamm. class B"

250 V: CSA-C22.2 No 1; UL1414

275 V: ENEC; CQC;

### MARKING

C-value; tolerance; rated voltage; sub-class; manufacturer's type designation; code for dielectric material; manufacturer location; manufacturer's emblem; year and week

### DIELECTRIC

Polypropylene film

### ELECTRODES

Metallized film

### CONSTRUCTION

Mono construction

### RATED VOLTAGE

AC 275 V; 50 to 60 Hz

### FEATURES

15 to 22.5 mm lead pitch. Supplied loose in box and taped on reel

Lead (Pb)-free product

RoHS compliant product



**RoHS**  
COMPLIANT

### PERMISSIBLE DC VOLTAGE

DC 630 V

### ENCAPSULATION

Plastic case, epoxy resin sealed, flame retardant UL-class 94 V-0

### CLIMATIC TESTING CLASS ACC. TO EN 60068-1

55/100/56/B

### CAPACITANCE RANGE (E12 SERIES)

E12 series 0.01 to 0.47  $\mu$ F

Preferred values acc. to E6

### CAPACITANCE TOLERANCE

$\pm 20 \%$ ;  $\pm 10 \%$

### LEADS

Tinned wire

### RATED TEMPERATURE

100 °C

### MAXIMUM APPLICATION TEMPERATURE

100 °C


### DETAIL SPECIFICATION

For more detailed data and test requirements, contact:

[RFI@vishay.com](mailto:RFI@vishay.com)



## COMPOSITION OF CATALOG NUMBER



## SPECIFIC REFERENCE DATA MKP 335 5 275 Vac

DESCRIPTION	VALUE	
Tangent of loss angle: C ≤ 100 nF 100 nF < C ≤ 470 nF	at 1 kHz	at 10 kHz
	≤ 7 x 10 <sup>-4</sup>	≤ 10 x 10 <sup>-4</sup>
	≤ 10 x 10 <sup>-4</sup>	≤ 20 x 10 <sup>-4</sup>
Rated voltage pulse slope (dU/dt) <sub>R</sub> at 385 Vdc	100 V/μs	
R between leads, for C ≤ 0.33 μF at 100 V; 1 min	> 15 000 MΩ	
RC between leads, for C > 0.33 μF at 100 V; 1 min	> 5000 s	
R between leads and case; 100 V; 1 min	> 30 000 MΩ	
Withstanding voltage DC (cut off current 10 mA); rise time 100 V/s	2200 V; 1 min	
Withstanding voltage AC between leads and case	2050 V; 1 min	





$U_{Rac} = 275 V$ ;  $C\text{-tol} = \pm 20 \%$

C ( $\mu F$ )	DIMENSIONS <sup>(1)</sup> w x h x l (mm)	MASS (g)	CATALOG NUMBER BFC2 335 ..... AND PACKAGING				
			LOOSE IN BOX				
			Short leads			Long leads	
			$l_t = 3.5 \pm 0.5 \text{ mm}$	$l_t = 5.0 \pm 1.0 \text{ mm}$	SPQ	$l_t = 25.0 \pm 2.0 \text{ mm}$	
			Last 5 digits of catalog number	Last 5 digits of catalog number		Last 5 digits of catalog number	SPQ
<b>Pitch = <math>15.0 \pm 0.4 \text{ mm}</math>; <math>d_t = 0.60 \pm 0.06 \text{ mm}</math></b>							
0.01	5.0 x 11.0 x 17.5	1.1	50103	56103	1250	54103	1000
0.015			50153	56153		54153	
0.022			50223	56223		54223	
0.033			50333	56333		54333	
0.047	6.0 x 12.0 x 17.5	1.4	50473	56473	1000	54473	1000
<b>Pitch = <math>15.0 \pm 0.4 \text{ mm}</math>; <math>d_t = 0.80 \pm 0.08 \text{ mm}</math></b>							
0.068	7.0 x 13.5 x 17.5	1.8	50683	56683	750	54683	500
0.1	8.5 x 15.0 x 17.5	2.3	50104	56104	750	54104	500
0.15	10.0 x 16.5 x 17.5	3.0	50154	56154	500	54154	450
<b>Pitch = <math>22.5 \pm 0.4 \text{ mm}</math>; <math>d_t = 0.80 \pm 0.08 \text{ mm}</math></b>							
0.22	8.5 x 18.0 x 26.0	4.1	50224	56224	200	54224	250
0.33	10.0 x 19.5 x 26.0	5.0	50334	56334	200	54334	200
0.47	12.0 x 22.0 x 26.0	6.9	50474	56474	150	54474	200


**Note**

(1) Specified dimensions only valid for  $\pm 20 \%$  tolerance values.


**MAXIMUM RMS VOLTAGE AND AC CURRENT (SINEWAVE) AS A FUNCTION OF FREQUENCY**



## CAPACITANCE



## IMPEDANCE



## APPROVALS

COUNTRY	SPECIFICATION	ELECTRICAL VALUES	FILE NUMBERS	APPROVAL MARK
U.S.A. (for AC 250 V)	UL1414	10 nF to 1.0 μF	E112471	
Canada (for AC 250 V)	CSA-C22.2 No.1	10 nF to 1.0 μF	1104861 (LR94054-16)	
China (for AC 275 V)	CQC	10 nF to 1.5 μF	CQC02001001482 (Shanghai factory) CQC03001004371 (Roeselare factory)	
CB TEST CERTIFICATE (for AC 275 V)		10 nF to 1.5 μF: 55/100/56/B	FI 1185 A2	
Europe (for AC 275 V)	EN132400 IEC 60384-14 2 <sup>nd</sup> edition	10 nF to 1.5 μF	14216	

## APPLICATION NOTES

- For X2 electromagnetic interference suppression in **across the line applications** (50/60 Hz) with a maximum mains voltage of 275 Vac.
- These capacitors are not intended for continuous pulse applications. For these situations, capacitors of the AC and pulse programs must be used.
- These capacitors are not intended for series impedance application. For these situations in case safety approvals are requested, please refer to our special capacitors of 1772 series with internal series connection.
- The maximum ambient temperature must not exceed 100 °C.
- Rated voltage pulse slope:  
If the pulse voltage is lower than the rated voltage, the values of the specific reference data can be multiplied by 385 Vdc and divided by the applied voltage.



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.