

# MMK22.5105K250D13L4TRAY

aka F601DD105K250C MMK22,5105K250D13L4TRAY

Capacitor, film, 1 uF, +/-10% Tol, -55/+100C, DC General Purpose, 250V@85C, Lead Spacing=22.5 mm



## Dimensions (mm)

ID	Dimension	Tolerance
L	26	max
H	14.5	max
T	6.5	max
S	22.5	+/-0.4
LL	5	nom
F	0.8	nom

## Specifications

Manufacturer:	KEMET
Brand:	Evox
Capacitance:	1 uF
Temperature Range:	-55/+100C
Rated Temperature:	85C
Voltage @ rated temp:	250V
Voltage AC:	160VAC
Tolerance:	+/-10%
Body Type:	Radial Box
Construction:	Non-inductive
Application:	DC General Purpose
Dielectric:	Metallized Polyester
Dissipation Factor @ 1 kHz:	0.8%
Dissipation Factor @ 10 kHz:	1.5%
Insulation Resistance:	10 GOhm
Inductance:	6 nH
Maximum dVdT:	8v/us
Miscellaneous Electrical:	CECC 30401-042, IEC 60384-2, DIN 44122 series(MMK)
Package Kind:	Bulk
Package Type:	Tray
Package Quantity:	234