


## Metallized Polyester Film Capacitors Related Document: IEC 60384-2

Dimensions in millimeters



### MAIN APPLICATIONS

Blocking, bypassing, filtering and timing, high frequency coupling and decoupling. Interference suppression in low voltage applications.

### MARKING

Manufacturer's logo/type/C-value/rated voltage/tolerance/date of manufacture

### DIELECTRIC

Polyester film

### ELECTRODES

Vacuum deposited aluminum

### COATING

Flame retardant plastic case (UL-class 94 V-0), epoxy resin sealed

### CONSTRUCTION

Extended metallized film (refer to general information)

### LEADS

Tinned wire

### IEC TEST CLASSIFICATION

55/100/56, according to IEC 60068

### OPERATING TEMPERATURE RANGE

- 55 °C to + 100 °C

### CAPACITANCE RANGE

1000 pF to 1.0 µF

### CAPACITANCE TOLERANCES

± 20 % (M), ± 10 % (K), ± 5 % (J)

### RATED VOLTAGES (U<sub>R</sub>)

63 V<sub>DC</sub>, 100 V<sub>DC</sub>, 250 V<sub>DC</sub>, 400 V<sub>DC</sub>, 630 V<sub>DC</sub>

### FEATURES

- Compliant to RoHS directive 2002/95/EC

### PERMISSIBLE AC VOLTAGES (RMS) UP TO 60 Hz

40 V<sub>AC</sub>, 63 V<sub>AC</sub>, 160 V<sub>AC</sub>, 200 V<sub>AC</sub>, 220 V<sub>AC</sub>

### TEST VOLTAGE (ELECTRODE/ELECTRODE)

1.6 x U<sub>R</sub> for 2 s

### INSULATION RESISTANCE

Measured with 100 V<sub>DC</sub> (63 V<sub>DC</sub> series at 50 V<sub>DC</sub>) after one minute

For C ≤ 0.33 µF and U<sub>R</sub> > 100 V<sub>DC</sub>:

30 000 MΩ minimum value (100,000 MΩ typical value)

For C ≤ 0.33 µF and U<sub>R</sub> ≤ 100 V<sub>DC</sub>:

15 000 MΩ minimum value (50 000 MΩ typical value)

### TIME CONSTANT

Measured at 100 V<sub>DC</sub> (63 V<sub>DC</sub> series measured at 50 V<sub>DC</sub>) after one minute

For C > 0.33 µF and U<sub>R</sub> ≤ 100 V<sub>DC</sub>:

5000 s minimum value (15 000 s typical value)

### CAPACITANCE DRIFT

Up to + 40 °C, ± 1.5 % for a period of two years

### DERATING FOR DC AND AC. CATEGORY VOLTAGE U<sub>C</sub>

At + 85 °C: U<sub>C</sub> = 1.0 U<sub>R</sub>

At + 100 °C: U<sub>C</sub> = 0.8 U<sub>R</sub>

### SELF INDUCTANCE

~ 6 nH measured with 2 mm long leads

### PULL TEST ON LEADS

≥ 30 N in direction of leads according to IEC 60068-2-21

### RELIABILITY

Operational life > 300 000 Hz

Failure rate < 2 FIT (40 °C and 0.5 x U<sub>R</sub>)



**RoHS**  
COMPLIANT

For further details, please refer to the general information available at [www.vishay.com/doc?26033](http://www.vishay.com/doc?26033).

**MAXIMUM PULSE RISE TIME**

PCM (mm)	Maximum Pulse Rise Time dV/dt [V/μs]				
	63 V <sub>DC</sub>	100 V <sub>DC</sub>	250 V <sub>DC</sub>	400 V <sub>DC</sub>	630 V <sub>DC</sub>
7.5	12	20	32	41	70

**Note**

If the maximum pulse voltage is less than the rated voltage higher dV/dt values can be permitted.

**DISSIPATION FACTOR TAN δ**

MEASURED AT	C ≤ 0.1 μF	0.1 μF < C ≤ 1.0 μF
1 kHz	8 x 10 <sup>-3</sup>	8 x 10 <sup>-3</sup>
10 kHz	15 x 10 <sup>-3</sup>	15 x 10 <sup>-3</sup>
100 kHz	25 x 10 <sup>-3</sup>	-
Maximum values		

CAPACITANCE	CAPACITANCE CODE	VOLTAGE CODE 06 63 V <sub>DC</sub> /40 V <sub>AC</sub>			VOLTAGE CODE 01 100 V <sub>DC</sub> /63 V <sub>AC</sub>			VOLTAGE CODE 25 250 V <sub>DC</sub> /160 V <sub>AC</sub>			VOLTAGE CODE 40 400 V <sub>DC</sub> /200 V <sub>AC</sub>			VOLTAGE CODE 63 <sup>(1)</sup> 630 V <sub>DC</sub> /220 V <sub>AC</sub>					
		W	H	L	W	H	L	W	H	L	W	H	L	W	H	L			
		1000 pF	-210	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	2.5
1500 pF	-215	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	2.5	7.5	10.0
2200 pF	-222	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	2.5	7.5	10.0
3300 pF	-233	-	-	-	-	-	-	-	-	-	2.5	7.5	10.0	3.0	8.5	10.0	-	-	-
4700 pF	-247	-	-	-	-	-	-	-	-	-	2.5	7.5	10.0	-	-	-	-	-	-
6800 pF	-268	-	-	-	-	-	-	-	-	-	2.5	7.5	10.0	-	-	-	-	-	-
0.01 μF	-310	-	-	-	-	-	-	2.5	7.5	10.0	3.0	8.5	10.0	-	-	-	-	-	-
0.015 μF	-315	-	-	-	-	-	-	2.5	7.5	10.0	-	-	-	-	-	-	-	-	-
0.022 μF	-322	-	-	-	2.5	7.5	10.0	3.0	8.5	10.0	-	-	-	-	-	-	-	-	-
0.033 μF	-333	-	-	-	2.5	7.5	10.0	3.0	8.5	10.0	-	-	-	-	-	-	-	-	-
0.047 μF	-347	-	-	-	2.5	7.5	10.0	4.0	9.0	10.0	-	-	-	-	-	-	-	-	-
0.068 μF	-368	-	-	-	2.5	7.5	10.0	4.5	9.5	10.0	-	-	-	-	-	-	-	-	-
0.1 μF	-410	2.5	7.5	10.0	3.0	8.5	10.0	5.0	10.5	10.3	-	-	-	-	-	-	-	-	-
0.15 μF	-415	2.5	7.5	10.0	3.0	8.5	10.0	-	-	-	-	-	-	-	-	-	-	-	-
0.22 μF	-422	3.0	8.5	10.0	4.0	9.0	10.0	-	-	-	-	-	-	-	-	-	-	-	-
0.33 μF	-433	4.0	9.0	10.0	5.0	10.5	10.3	-	-	-	-	-	-	-	-	-	-	-	-
0.47 μF	-447	4.5	9.5	10.0	5.7	11.5	10.3	-	-	-	-	-	-	-	-	-	-	-	-
0.68 μF	-468	5.0	10.5	10.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
1.0 μF	-510	5.7	11.5	10.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

**Notes**

- Further values upon request

<sup>(1)</sup> Not suitable for mains applications.


Please refer to X-capacitors in our catalog "RFI Suppression Components".

**RECOMMENDED PACKAGING**


LETTER CODE	TYPE OF PACKAGING	HEIGHT (H) (mm)	REEL DIAMETER (mm)	ORDERING CODE EXAMPLE	PCM 7.5
D	Ammo	16.5	S <sup>(1)</sup>	MKT 1818-310-255-D	X
G	Ammo	18.5	S <sup>(1)</sup>	MKT 1818-310-255-G	X
F	Reel	16.5	350	MKT 1818-310-255-F	X
W	Reel	18.5	350	MKT 1818-310-255-W	X
-	Bulk	-	-	MKT 1818-310-255	X

**Note**


<sup>(1)</sup> S = box size 55 mm x 210 mm x 340 mm (W x H x L)




Permissible AC Voltage versus Frequency




Permissible AC Voltage versus Frequency



Permissible AC Voltage versus Frequency



Permissible AC Voltage versus Frequency



Permissible AC Voltage versus Frequency



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.