

Type SSQ

Square Ceramic Surface Mount Quick Acting Fuse

2410 Size
RoHS 6 Compliant

SSQD0808



Electrical Characteristics (UL/CSA STD.248-14)

Testing current	Blow Time	
	Minimum	Maximum
100%	4 Hrs.	N/A
200%	N/A	5 Sec

Approvals



Safety Agency Approvals	Amp range / Volt @ I.R.ability
Certified File No. LR39772	100mA - 7A / 125V @ 50A AC
Listed File No. E20624	100mA - 7A / 125V @ 50A AC and 86V @ 10,000A DC and 125V @ 300A DC 7.1A - 12A / 125V @ 50A AC and 86V @ 10,000A DC
Recognized File No. E20624	15A / 86V @ 10,000A DC

RoHS 6 Compliant Product

RoHS Reflow Reference : JEDEC J-STD-020C (260°C, 40 sec max)
RoHS Wave Soldering Compatible : (260°C, 10 sec max)

Environmental Specification

Shock Resistance

MIL-STD-202G, Method 213B, Test Condition I
(100 G's peak for 6 milliseconds; Sawtooth Waveform)

Vibration Resistance

MIL-STD-202G, Method 201A (10-55 Hz, 0.06 inch, total excursion)

Salt Spray Resistance

MIL-STD-202G, Method 101E, Test condition B (48 hrs)

Insulation Resistance

MIL-STD-202G, Method 302, Test Condition A
(After Opening) 10,000 ohms minimum

Solderability

MIL-STD-202G, Method 208H

Soldering Heat Resistance

MIL-STD-202G Method 210F, Test Condition C. Top Side
(260°C, 20 sec)
MIL-STD-202G Method 210F, Test Condition D. Bottom Side
(260°C, 10sec)

Thermal Shock Resistance

MIL-STD-202G, Method 107G, Test Condition B
(-65°C to +125°C)

Operating Temperature

-55°C to +125°C

Catalog Number	Ampere Rating	Typical Cold Resistance (ohm)	Volt-drop @100% I_n (Volt) max.	Melting $I^2T < 10$ mSec (A ² Sec)	Melting $I^2T @ 10' I_n$ (A ² Sec)	Maximum Power Dissipation (W)
SSQ 250	250mA	0.65	0.30	0.02	0.01	0.07
SSQ 375	375mA	0.36	0.25	0.04	0.03	0.09
SSQ 500	500mA	0.24	0.22	0.07	0.06	0.11
SSQ 750	750mA	0.15	0.17	0.11	0.07	0.13
SSQ 1	1A	0.11	0.17	0.19	0.14	0.17
SSQ 1.25	1.25A	0.09	0.16	0.33	0.24	0.20
SSQ 1.5	1.5A	0.07	0.15	0.57	0.41	0.23
SSQ 2	2A	0.05	0.15	1.0	0.8	0.30
SSQ 2.5	2.5A	0.038	0.14	1.7	1.4	0.36
SSQ 3	3A	0.028	0.13	3.0	2.4	0.43
SSQ 3.5	3.5A	0.025	0.13	3.9	3.3	0.47
SSQ 4	4A	0.022	0.13	5.1	4.4	0.51
SSQ 5	5A	0.016	0.12	8.8	7.8	0.62
SSQ 6.3	6.3A	0.012	0.12	15	14	0.74
SSQ 7	7A	0.011	0.114	20	19	0.81
SSQ 8	8A	0.009	0.112	26	25	0.89
SSQ 10	10A	0.007	0.107	46	44	1.07
SSQ 12	12A	0.006	0.103	70	69	1.24
SSQ 15	15A	0.004	0.098	121	124	1.54

Consult manufacturer for other ratings

Physical Specification

Materials

Ceramic body / Palladium Plated Brass Caps

Marking

On fuse:

"Current Rating" in black color, "bel" stamped in end caps

On label:


"bel", "SSQ", "Current Rating", "Voltage Rating", "Interrupting Rating",

"Appropriate Safety Logos" and "UL", "CE" (China RoHS compliant)

Packaging

5,000 fuses in 13 inches dia. reel, 12mm wide tape, 4mm pitch, per EIA Standard 481

Mechanical Dimensions



ORDERING INFORMATION SEE LAST 2 PAGES

Type SSQ


Square Ceramic Surface Mount Quick Acting Fuse

2410 Size
RoHS 6 Compliant



SSQC0808

SSQ - TIME CURRENT CHARACTERISTIC CURVE



Specifications subject to change without notice

NOTE - see important information under "User Guide" on P.08

Corporate Office

Bel Fuse Inc.

206 Van Vorst Street, Jersey City, NJ 07302
Tel: 201-432-0463
Fax: 201-432-9542
E-Mail: belfuse@belfuse.com
Website: www.belfuse.com

Far East Office

Bel Fuse Ltd.

8F/8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel: 852-2328-5515
Fax: 852-2352-3706

European Office

Bel Fuse Europe Ltd.

Preston Technology Management Centre
Marsh Lane, Preston PR1 8UQ
Lancashire, U.K
Tel: 44-1772-556601
Fax: 44-1772-888366