



Home > Products > Discrete Thermistors > 175 > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

175-104LAF-301



Surface mounted device 1206

Actual product appearance may vary.

Features

Surface mountable for automated pick and place
 Glass-coated ceramic for long term reliability
 Solder plated nickel
 Versatile
 Solderable leads
 Available on tape and reel

Potential Applications

Consumer electronics
 PCB temperature sensing
 Communications
 Computers
 Rechargeable battery packs
 Low-cost applications with a maximum temperature of 150 °C [302 °F]
 Automotive

Description

173 Series and 175 Series Thermistors are designed to be mounted using robotics onto rigid or flexible PC boards. They are particularly suited for PC boards with a high density of discrete components. The solder-plated, nickel barrier terminations are easily soldered and meet ANSI/JSTD-002 Method B. These products are designed to withstand solder temperatures of 260 °C for 30 seconds. Available on tape and reel for automated assembly.

My Links

[Login to iCOM](#)
[Login as Rep/AD](#)
[Login as Guest](#)
[Login to Digital University](#)

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

[Specification Search](#)

Supporting Documentation

None Available

Product Specifications	
Availability	Global
Nominal Resistance at 25 °C [77 °F]	100,000 Ohm
Tolerance	± 5.0%
Accuracy	25 °C [77 °F]
R - T Curve	16
Operating Temperature Range	-60 °C to 125 °C [-76 °F to 257 °F]
Maximum Diameter	EIA 1206 SMD
Time Constant in Air	10.0 s
Dissipation Constant	3,5 m/W°C
Series Name	175