


VDSL SINGLE PORT CPE FILTER MODULES

For Infineon 4-band VDSL Chipsets



- Single port CPE filter module for 4-band VDSL NT applications (Plan 998)
- Matched to Infineon PEF22814/22815 4-band VDSL chipsets
- Multi-function model includes: HPF Splitter, Hybrid Transformer, TX and RX Separation Filters and Common Mode Choke
- Designed to meet IEC950 supplementary insulation requirements

Electrical Specifications @ 25°C — Operating Temperature -40°C to +85°C

Part Number	Line to RX Specifications			Transhybrid Loss @ 0.138 - 3.4MHz and 5.7 - 8.1MHz	Transhybrid Loss @ 4.0 - 5.04MHz and 9.1 - 11.9MHz	Line Return Loss @ 0.138 - 3.4MHz and 5.7 - 8.1MHz
	Passband @ 0.138 - 3.4MHz and 5.7 - 8.1MHz	Stopband Frequency	Attenuation (relative to Passband)			
BX4045	Nominal Gain 7.5dB (TYP)	10 - 60kHz	40dB (MIN)	25dB (MIN)	37dB (MIN)	12dB (MIN)
		4 - 5.04MHz	17dB (MIN)			
	Ripple 2.5dB (MAX)	9.1 - 11.9MHz	17dB (MIN)			
		26 - 40MHz	26dB (MIN)			
Part Number	Line to RX Specifications			Transhybrid Loss @ 0.9 - 3.4MHz and 5.7 - 8.1MHz	Transhybrid Loss @ 4.0 - 5.04MHz and 9.1 - 11.9MHz	Line Return Loss @ 0.9 - 3.4MHz and 5.7 - 8.1MHz
	Passband @ 0.138 - 3.4MHz and 5.7 - 8.1MHz	Stopband Frequency	Attenuation (relative to Passband)			
BX4042	Nominal Gain 7.5dB (TYP)	10 - 220kHz	60dB (MIN)	30dB (MIN)	37dB (MIN)	12dB (MIN)
		4 - 5.04MHz	17dB (MIN)			
	Ripple 1.5dB (MAX)	9.1 - 11.9MHz	17dB (MIN)			
		26 - 40MHz	26dB (MIN)			


Electrical Specifications @ 25°C — Operating Temperature -40°C to +85°C

Part Number	TX to Line Specifications			Isolation Voltage (V _{rms})	Line Impedance (Ω)	TX Impedance (Ω)	RX Impedance (Ω)
	Passband @ 4.0 - 5.04MHz and 9.1 - 11.9MHz	Stopband Frequency	Attenuation (relative to Passband)				
BX4045	Nominal Gain 4.0dB (TYP)	10 - 60kHz	40dB (MIN)	1500	120	40	270
BX4042		(BX4042: up to 150MHz)	22dB (MIN)				
	Ripple 2.5dB (MAX)	22 - 40MHz	22dB (MIN)				

NOTE: BX4045 for 4-band plan 998: 138kHz starting frequency — BX4042 for 4-band plan 998: 900kHz starting frequency

Mechanical

BX4045/BX4042



	BX4042	BX4045
Weight.....	6.8 grams	8.0 grams
Tray.....	30/tray	30/tray
Dimensions: Inches		
mm		
Unless otherwise specified, all tolerances are ± .010 / 0.25		


VDSL SINGLE PORT CPE FILTER MODULES

For Infineon 4-band VDSL Chipsets



Schematic

BX4045/BX4042



For More Information :

UNITED STATES (Worldwide)	UNITED KINGDOM (Northern Europe)	FRANCE (Southern Europe)	SINGAPORE (Southern Asia)	TAIWAN, R.O.C. (Northern Asia)	HONG KONG (China/Hong Kong)	DISTRIBUTOR
12220 World Trade Drive San Diego, CA 92128 U.S.A. http://www.pulseeng.com TEL: 858 674 8100 FAX: 858 674 8262	1 & 2 Huxley Road The Surrey Research Park Guildford, Surrey GU2 5RE United Kingdom TEL: 44 1483 401700 FAX: 44 1483 401701	Zone Industrielle F-39270 Orgelet France TEL: 33 3 84 35 04 04 FAX: 33 3 84 25 46 41	150 Kampong Ampat #07-01/02 KA Centre Singapore 368324 TEL: 65 6287 8998 FAX: 65 6280 0080	3F-4, No. 81, Sec. 1 HsinTai Wu Road Hsi-Chih, Taipei Hsien Taiwan, R.O.C. Tel: 886 2 2698 0228 FAX: 886 2 2698 0948	9/F, Phase 2, Tai Sang Shatin Warehouse Centre 6 Wong Chuk Yeung Street Fotan, Shatin, Hong Kong TEL: 852 2788 6588 FAX: 852 2776 1055	

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

Printed on recycled paper. ©2004, Pulse Engineering, Inc. All Rights Reserved.

B833.A (1/04)