muRata	Denien			English	中文(简体)	日本語
machine Region		Europe	Part Number Search			Search
Home	Products	" Search	Support		About Us	.:
Home> Search E	ngine > Catalog: SFELF10M7LF	TABO				

Filters for Audio Visual Equipment > Ceramic Filters for FM

How to check EU RoHS Comliant of Our Products is here.

Product Lifecycle Stage	in Production
Recommended Rank	Preferred

Specification

Global Part Number	SFELF10M7LFTA-B0
Previous Part Number	
Center Frequency (fo)	
Nominal Center Frequency (fn)	10.700MHz
3dB Bandwidth	fn±25kHz min.
Attenuation	280kHz max.
Area of Attenuation	[within 20dB]
Insertion Loss (at minimum loss point)	7.0dB ±2.0dB
Ripple (within 3dB B.W.)	1.0dB max.
Spurious Attenuation(1)	30dB min.
Area of Spurious Attenuation(1)	[within 9MHz to fn]
Spurious Attenuation(2)	30dB min.
Area of Spurious Attenuation(2)	[within fn to 12MHz]
GDT Bandwidth	
Area of GDT Bandwidth	
Input/Output Impedance	330ohm
Elements	2

Details

- PDF Part Numbering ? Appearance ? **Dimensions** ? ð Features_and_Applications ? 2 Frequency_Characteristics Spurious Response ? Test Circuit ? ð Notice (storage and operating condition) ? Notice (soldering and mounting) ? E1 Notice (handling) ? PDF
 - Packaging

Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	
330mm Paper Tape	
330mm Embossed Tape	
Bulk Case	
Bulk(Bag)	500
Ammo Pack	1500
320Reel	
Magazine	
Box	

Please approve our product specifications or to transact the approval sheet for product specifications before ordering. Please read rating and !Cautions first. Product specifications in this catalog are as of January 2008.

All products and company names herein are trademarks or registered trademarks of their respective owners.