


Thick Film Resistor Networks Military, MIL-PRF-83401 Qualified, Type RZ Dual-In-Line Package, 01, 03, 05 Schematics



FEATURES

- MIL-PRF-83401 qualified
- Epoxy molded construction
- All device leads are hot-solder dipped
- Available in tube pack
- TCR available in "K" (± 100 ppm/ $^{\circ}$ C) or "M" (± 300 ppm/ $^{\circ}$ C) depending on style
- 100 % screen tested per Group A, Subgroup 1 of MIL-PRF-83401
- All devices are capable of passing the MIL-STD-202, Method 210, Condition D, "Resistance to Soldering Heat" test

STANDARD ELECTRICAL SPECIFICATIONS

| VISHAY DALE MODEL/ PINS NO | SCHEMATIC | RESISTOR POWER RATING MAX. at 70 $^{\circ}$ C W | PACKAGE POWER RATING MAX. at 70 $^{\circ}$ C W | RESISTANCE RANGE Ω | STANDARD TOLERANCE \pm % | TEMPERATURE COEFFICIENT (- 55 $^{\circ}$ C to + 125 $^{\circ}$ C) | WEIGHT g |
|----------------------------|-----------|---|--|---------------------------|---|---|----------|
| MDM 14 | 01 | 0.10 | 1.30 | 10 - 1M | ± 2 ($\pm 1, \pm 5$) ⁽²⁾ | K, M ⁽¹⁾ | 1.3 |
| MDM 14 | 03 | 0.20 | 1.40 | 10 - 1M | ± 2 ($\pm 1, \pm 5$) ⁽²⁾ | K, M ⁽¹⁾ | 1.3 |
| MDM 14 | 05 | 0.05 | 1.20 | Consult factory | ± 2 ($\pm 1, \pm 5$) ⁽²⁾ | K, M ⁽¹⁾ | 1.3 |
| MDM 16 | 01 | 0.10 | 1.50 | 10 - 1M | ± 2 ($\pm 1, \pm 5$) ⁽²⁾ | K, M ⁽¹⁾ | 1.5 |
| MDM 16 | 03 | 0.20 | 1.60 | 10 - 1M | ± 2 ($\pm 1, \pm 5$) ⁽²⁾ | K, M ⁽¹⁾ | 1.5 |
| MDM 16 | 05 | 0.05 | 1.40 | Consult factory | ± 2 ($\pm 1, \pm 5$) ⁽²⁾ | K, M ⁽¹⁾ | 1.5 |


Notes

⁽¹⁾ K = ± 100 ppm/ $^{\circ}$ C; M = ± 300 ppm/ $^{\circ}$ C


⁽²⁾ ± 1 % and ± 5 % tolerances available on request

GLOBAL PART NUMBER INFORMATION


New Global Part Numbering: M8340101M2201GBD04 (preferred part numbering format)




Historical Part Number example: M8340101M2201GB (will continue to be accepted)



New Global Part Numbering: M8340102KA001GJD04 (preferred part numbering format)



Historical Part Number example: M8340102KA001GJ (will continue to be accepted)






MDM (Military M83401)

Thick Film Resistor Networks Military, MIL-PRF-83401 Qualified, Vishay Dale
Type RZ Dual-In-Line Package, 01, 03, 05 Schematics

DIMENSIONS in inches [millimeters]



| VISHAY DALE MODEL | A | B | C |
|-------------------|---------------|---------------|---|
| MDM14 | 0.750 [19.05] | 0.600 [15.24] | 6 |
| MDM16 | 0.850 [21.59] | 0.700 [17.78] | 7 |

| IMPEDANCE CODES | | | | | |
|-----------------|--------------------|--------------------|------|--------------------|--------------------|
| CODE | R ₁ (Ω) | R ₂ (Ω) | CODE | R ₁ (Ω) | R ₂ (Ω) |
| A001 | 82 | 130 | A010 | 330 | 470 |
| A002 | 120 | 200 | A011 | 330 | 680 |
| A003 | 130 | 210 | A012 | 1.5K | 3.3K |
| A004 | 160 | 260 | A013 | 3K | 6.2K |
| A005 | 180 | 240 | A014 | 180 | 270 |
| A006 | 180 | 390 | A015 | 270 | 270 |
| A007 | 220 | 270 | A016 | 560 | 560 |
| A008 | 220 | 330 | A017 | 560 | 1.2K |
| A009 | 330 | 390 | A018 | 620 | 2.7K |

| TECHNICAL SPECIFICATIONS | | |
|-----------------------------------|------------------|---------------|
| PARAMETER | UNIT | MDM SERIES |
| Maximum Operating Voltage | V _{DC} | 100 |
| Voltage Coefficient of Resistance | V _{eff} | < 50 ppm |
| Dielectric Strength | V _{AC} | 200 per min. |
| Insulation Resistance | Ω | 10 000 M |
| Operating Temperature Range | °C | - 55 to + 125 |
| Storage Temperature Range | °C | - 55 to + 150 |

| MECHANICAL SPECIFICATIONS | |
|--------------------------------|--------------------------------------|
| Marking Resistance to Solvents | Permanency testing per MIL-PRF-83401 |
| Solderability | Per MIL-PRF-83401 |
| Body | Molded epoxy |
| Terminals | Copper alloy, hot-solder dipped |

MDM (Military M83401)




Vishay Dale Thick Film Resistor Networks Military, MIL-PRF-83401 Qualified, Type RZ Dual-In-Line Package, 01, 03, 05 Schematics


| CIRCUIT APPLICATIONS | |
|----------------------------|--|
| <p>01 SCHEMATIC</p> | <p>MDM1401 (M8340101xxxxxB) MDM1601 (M8340102xxxxxB)</p> <p>13 or 15 resistors with one pin common</p> <p>The MDMxx01 provides the user with a choice of 13 or 15 nominally equal resistors, each connected to a common pin. Commonly used in the following applications:</p> <ul style="list-style-type: none"> • MOS/ROM Pull-up/Pull-down • Open Collector Pull-up • "Wired OR" Pull-up • Power Driven Pull-up • TTL Input Pull-down • Digital Pulse Squaring • TTL Unused Gate Pull-up • High Speed Parallel Pull-up |
| <p>03 SCHEMATIC</p> | <p>MDM1403 (M8340101xxxxxA) MDM1603 (M8340102xxxxxA)</p> <p>7 or 8 isolated resistors</p> <p>The MDMxx03 provides the user with a choice of 7 or 8 nominally equal resistors, with each resistor isolated from all others. Commonly used in the following applications:</p> <ul style="list-style-type: none"> • "Wired OR" Pull-up • Power Driven Pull-up • Line Termination • Long-line Impedance Balancing • LED Current Limiting • ECL Output Pull-down • TTL Input Pull-down |
| <p>05 SCHEMATIC</p> | <p>MDM1405 (M8340101xxxxxJ) MDM1605 (M8340102xxxxxJ)</p> <p>12 or 14 resistor pairs</p> <p>The MDMxx05 provides the user with a choice of 12 or 14 pairs of R1/R2 resistor values for pulse squaring and TTL dual-line terminating requirements.</p> |

CAGE CODE: 91637


01 Schematic



03 Schematic



05 Schematic





MDM (Military M83401)

Thick Film Resistor Networks Military, MIL-PRF-83401 Qualified, Vishay Dale
Type RZ Dual-In-Line Package, 01, 03, 05 Schematics

| PERFORMANCE | | |
|---------------------------------|--|--|
| TEST | CONDITIONS | MAX. ΔR (Typical Test Lots) |
| Power Conditioning | 1.5 x rated power, applied 1.5 h "ON" and 0.5 h "OFF" for 100 h \pm 4 h at + 25 °C ambient temperature | \pm 0.50 % ΔR |
| Thermal Shock | 5 cycles between - 65 °C and + 125 °C | \pm 0.50 % ΔR |
| Short Time Overload | 2.5 x rated working voltage for 5 s | \pm 0.25 % ΔR (Char. K) \pm 0.50 % ΔR (Char. M) |
| Low Temperature Operation | 45 min at full rated working voltage at - 65 °C | \pm 0.25 % ΔR (Char. K) \pm 0.50 % ΔR (Char. M) |
| Moisture Resistance | 240 h with humidity ranging from 80 % RH to 98 % RH | \pm 0.50 % ΔR |
| Resistance to Soldering Heat | Leads immersed in + 260 °C solder to within 1/16" of body for 10 s | \pm 0.25 % ΔR |
| Shock | Total of 18 shocks at 100 G's | \pm 0.25 % ΔR |
| Vibration | 12 h at maximum of 20 G's between 10 and 2000 Hz | \pm 0.25 % ΔR |
| Load Life | 1000 h at + 70 °C, rated power applied 1.5 h "ON", 0.5 h "OFF" for full 1000 h period | \pm 0.50 % ΔR (Char. K) \pm 2.00 % ΔR (Char. M) |
| Terminal Strength | 4.5 pound pull for 30 s | \pm 0.25 % ΔR |
| Insulation Resistance | 10 000 M Ω (minimum) | - |
| Dielectric Withstanding Voltage | No evidence of arcing or damage (200 V _{RMS} for 1 min) | - |



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.