

Fully Sealed Container Cermet Potentiometers Military and Professional Grade


P13V

P13T

P13 potentiometers fully conform to CECC 41301-001 specification. Their excellent performances are due to the use of a cermet-track sealed in a large case.

P13 interchangeability with RV6, combined with the excellent stability of its rated characteristics make it fully acceptable for military and professional uses.

FEATURES


- High power rating 1.5 Watt at 70 °C
- CECC 41 301-001 (A, B, C)
- GAM T1
- Fully sealed case
- Tight temperature coefficient (± 75 ppm/°C typical)
- Mechanical strength




DIMENSIONS in millimeters

P13T - (PC32) A

PANEL CUTOUT




CIRCUIT DIAGRAM




P13Q - B

PANEL CUTOUT




P13H




P13V - (PC33) C

PANEL CUTOUT




P13V DBAN




Panel sealed version

P13TP - P13TPE

TPE: Including locating ped




P13T - F55




Panel sealed version

P13VP - P13VPE

VPE: Including locating ped



PANEL CUTOUT



Undergoes European Quality Insurance System

ELECTRICAL SPECIFICATIONS



Resistive Element		cermet
Electrical Travel		270° ± 10°
Resistance Range	Linear Law	22 Ω to 10 MΩ
	Logarithmic Laws	100 Ω to 2.2 MΩ
Standard series E3		1 - 2.2 - 4.7 and on request 1 - 2 - 5
Tolerance	Standard	± 20 %
	On Request	± 10 % - ± 5 %
Power Rating	Linear	1.5 W at + 70 °C
	Logarithmic	0.75 W at + 70 °C
Temperature Coefficient		See Standard Resistance Element Data
Limiting Element Voltage (Linear Law)		350 V
Contact Resistance Variation		3 % Rn or 3 Ω
End Resistance (Typical)		1 Ω
Dielectric Strength (RMS)		2000 V
Insulation Resistance (500 VDC)		10 ⁶ MΩ

MECHANICAL SPECIFICATIONS

Mechanical Travel	$300^\circ \pm 5^\circ$
Operating Torque (max. Ncm)	2 typical
End Stop Torque (max. Ncm)	style T.Q.: 35 - V: 80
Tightening Torque (max. Ncm)	T.Q.: 150 - V: 250
Unit Weight (max. g)	6 to 18

ENVIRONMENTAL SPECIFICATIONS

Temperature Range	-55°C to $+125^\circ \text{C}$
Climatic Category	55/100/56
Sealing	fully sealed container IP67

POWER RATING CHART**RESISTANCE LAWS****TEMPERATURE COEFFICIENT**

For values $\geq 100 \text{ ohms}$ and in the temperature range $+20^\circ \text{C}$ to $+70^\circ \text{C}$, the typical temperature coefficient is $\pm 75 \text{ ppm}/^\circ \text{C}$.



PERFORMANCE					
NF C 83-253				TYPICAL VALUES AND DRIFTS	
TESTS	CONDITIONS	$\frac{\Delta RT}{RT}$ (%)	REQUIREMENTS	$\frac{\Delta R_{1-2}}{R_{1-2}}$ (%)	$\frac{\Delta RT}{RT}$ (%) $\frac{\Delta R_{1-2}}{R_{1-2}}$ (%)
Climatic Sequence	Phase A dry heat 125 °C Phase B damp heat Phase C cold - 55 °C Phase D damp heat 5 cycles	± 10 %		± 10 %	± 0.5 % ± 1 %
Long Term Damp Heat	56 days 40 °C 93 % RH	± 10 %		± 10 %	± 0.5 % ± 1 % Dielectric strength: 1000 V Insulation resistance: > 10 ⁴ MΩ
Rotational Life	25 000 cycles	± 10 %			± 3 % Contact res. variation: < 2 % R _n
Load Life	1000 h at rated power 90°/30° - ambient temp. 70 °C	± 10 %			± 1 % Contact res. variation: < 3 % R _n
Rapid Temperature Change	5 cycles - 55 °C at + 125 °C	± 3 %			± 0.5 %
Shocks	50 g at 11 ms 3 successive shocks in 3 directions	± 2 %			± 0.1 % ± 0.2 %
Vibrations	10 - 55 Hz 0.75 mm or 10 g during 6 hours	± 2 %			± 0.1 % $\frac{\Delta V_{1-2}}{V_{1-3}} < \pm 0.2 \%$

STANDARD RESISTANCE ELEMENT DATA							
STANDARD RESISTANCE VALUES	LINEAR LAW			LOGS LAW			TCR - 55 °C + 125 °C
	MAX. POWER AT 70 °C	MAX. WORKING VOLTAGE	MAX. WIPER CUR.	MAX. POWER AT 70 °C	MAX. WORKING VOLTAGE	MAX. WIPER CUR.	
Ω	W	V	mA	W	V	mA	ppm/°C
22 47	1.5	5.74 8.4	261 177				0 + 200
100 220 470 1K 2.2K 4.7K 10K 22K 47K 100K 220K 470K 1M 2.2M 4.7M 10M	↓ 1.5 1.22 0.56 0.26 0.12 0.05 0.026 0.012	12.2 18.2 26.5 38.7 57.5 84 122.5 182 265 350 350 350 350 350 350 350	122 82.6 56.5 38.7 26.1 17.9 12.2 8.26 5.65 3.5 1.6 0.74 0.35 0.16 0.074 0.035	0.75 ↓ 0.75 0.56 0.26 0.12 0.05	27 40 59 87 128 187 273 350 350 350 350 350 350 350 350	27 18 12 8.7 5.8 3.9 2.7 1.6 0.74 0.35 0.16	± 100

MARKING

Printed:

- VISHAY trademark
- series
- style
- ohmic value (in Ω, kΩ or MΩ)
- tolerance (in %)
- resistance law
- manufacturing date
- marking of terminals a

SPECIAL FEATURES PANEL SEALING

Potentiometers P13T and P13V can be fitted with a device providing sealing between the threaded bushing and the front panel. Their designation is P13TP and P13VP respectively or with a locating peg P13TPE and P13VPE.

SHAFT

Shaft lengths are measured from the mounting surface to the free end of the potentiometer. Special shafts are available, provided customer supplies a drawing.

The shaft slot is aligned to the wiper within ± 10°.

SHAFT LOCKING

On potentiometers equipped with a 3 mm Ø shaft, shaft locking can be obtained:

- either by a taper nut tightening a slotted bushing. Ask for P13H type. These devices are normally equipped with an L type shaft (12.5 mm with a slot),
 - or by a tightening nut locked by a screw. Ask for ES1 type.
- On potentiometers equipped with a Ø 6 mm shaft, locking can be obtained by a taper nut applying pressure on a slotted notched washer. This device is supplied in a box as an accessory. Ask for DBAN.

These devices are ordered separately. Please consult VISHAY SFERNICE.

ORDERING INFORMATION

P13	T	P OR PE	M	22 k Ω	$\pm 20\%$	A	XX	BO
SERIES	STYLE	PANEL SEALING	SHAFT	OHMIC VALUE	TOLERANCE	LAW	SPECIAL FEATURES	PACKAGING
	T 6 mm dia, 3 mm dia. shaft		K 9.5 mm, slotted M 12.5 mm, slotted R 22 mm, plain		$\pm 20\%$ standard $\pm 10\%$ on request	A Linear L clockwise logarithmic F inverse clockwise logarithmic	F55 DBAN F32 (PCB style)	
	Q 7 mm dia, 4 mm dia. shaft		E 9.5 mm, slotted F 12.5 mm, slotted G 22 mm, plain					
	V 10 mm dia, 6 mm dia. shaft		AC 16 mm, slotted AM 25 mm, slotted AL 50 mm, plain					
	locking H 6 mm dia, 3 mm dia. shaft		L 12.5 mm, slotted AP special shafts					
	VP 9.5 mm dia, 6 mm dia. shaft		AC 13 mm, slotted AM 22 mm, slotted AL 47 mm, plain					

SAP PART NUMBERING GUIDELINES

P	1	3	T	A	B	2	2	3	M	A	B	1	7				
MODEL			BUSHING	SHAFT		OHMIC VALUE			TOL	LAW	PACKAGING		SPECIAL (IF APPLICABLE)				

See the end of this data book for conversion tables



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.