



Search Results

Home > Products Overview > Search Results >

Evaluate

- FAQ's
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Current refinements (click to remove) Search Tips Within Results

Text Search: 'UTPCH15ORY'

Your search criteria matched only one product, shown below

UTPCH15ORY



- Exceed TIA/EIA568-B.2 Category 5e and ISO11801 Class D standards
- Each patch cord is 100% performance tested and wired T568A
- Constructed of Category 5e, 24 AWG UTP stranded cable and Pan-Plug[®] Modular Plugs; plug contacts plated with 50 microinches of gold for superior performance
- Plug meets all applicable TIA -968-A-3 requirements and exceeds IEC 60603 -7 specifications
- Patented tangle free latch prevents snags and provides easy release, saving time on frequent moves, adds, and changes
- Labels on patch cords provide identification of performance level, length, and quality control number
- Optional Patch Cord Color Bands snap on and off individual patch cables offering endless color coding options
- Optional RJ45 Plug Lock -In Device blocks unauthorized removal of cable, IP phone, other networking equipment or critical connection
- Third party tested to Category 5e component compliance

| | |
|------------------------------|--|
| Part Number | UTPCH15ORY |
| RoHS Compliancy Status | Compliant |
| Part Description | Category 5e, UTP patch cord with PanPlug [™] Modular Plugs on each end. |
| Product Type | Copper Patch Cord |
| Color | Orange |
| Length (ft.) | 15 |
| Length (m) | 4.57 |
| Boot Color | No Boot |
| Cable Color | Orange |
| Cable Type | UTP |
| Flammability Rating | CM |
| Performance Level | Category 5e |
| Pricing Description | Copper Patch Cord, Category 5e, Orange UTP Cable, 15 Feet |
| Wiring Scheme | T568A |
| Min. Order UOM | PC |
| Min. Order Qty. | 1 |
| BOM Qty. (# of Pkgs.) | <input type="text" value="0"/> |
| Add to Favorite Product List | |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.