




THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



**NOTES:**

1. SEE SHEET 2 FOR PRODUCT DESCRIPTIONS AND TECHNICAL SPECIFICATIONS.
2. SEE CURRENT CATALOG FOR PATCH CORD LENGTHS AND PACKAGE QUANTITY.
3. FOR LENGTHS OTHER THAN THOSE LISTED IN CATALOG, CONTACT YOUR PANDUIT SALES PERSON.
4. TESTED TO EIA/TIA 568-B.3.
5. PATCH CORD ROUTING CONFIGURATION A TO B.
6. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF RoHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.

										<b>FIBER OPTIC PATCH CORD</b> <b>FJ OPTI-PLUG TO ST CONFIGURATION</b> <b>CUSTOMER DRAWING</b>					
										 <b>PANDUIT</b> ™ CORP. TINLEY PARK, ILL 60477					
										 THIRD ANGLE PROJECTION		ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: (.X) (.XXX) ±.010 (0.3) (.XX) ±.03 (0.8) ANGLES		DRAWING FILENAME <b>M02779BJ_DC_00A.prt</b> SCALE <b>NONE</b>	
										DRAWN BY <b>MC</b>		REVIEW DRAWING NUMBERS		PART NO. <b>SEE TABLE, SHT. 2</b>	
										DATE <b>05-10-07</b>		DRAWING NO. <b>02779-16</b> (SHT. 1 of 2)		SIZE <b>A</b>	
										CHECK'D					
R	06-05-07	MC		RELEASED TO PRODUCTION	02779-16										
REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	OTH						

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.




FJ OPTI-PLUG TO ST FIBER OPTIC PATCH CORD

PANDUIT PART NO.	CABLE				FJ OPTI-PLUG			ST CONNECTOR		
	RATING	FIBER TYPE	COUNT	COLOR	MAX. IL	MIN. RL	COLOR	MAX. IL	MIN. RL	COLOR
F5D6P-2M*Y	RISER (OFNR)	50/125um OM2	DUPLX 3.0mm ZIPCARD	ORANGE	0.30dB	20dB	ELECTRIC IVORY	0.30dB	20dB	METALLIC FINISH
F6D6P-2M*Y		62.5/125um OM1		ORANGE	0.30dB	20dB	ELECTRIC IVORY	0.30dB	20dB	METALLIC FINISH
F9D6P-2M*Y		9/125um OS1		YELLOW	0.75dB	55dB	BLUE	0.75dB	55dB	METALLIC FINISH

\* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET

REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	OTH
R	06-05-07	MC		RELEASED TO PRODUCTION	02779-16				

FIBER OPTIC PATCH CORD FJ OPTI-PLUG TO ST CONFIGURATION CUSTOMER DRAWING									
									
 THIRD ANGLE PROJECTION					ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: (.X) (.XX) ± .03 (0.8) ANGLES (.XXX) ± .010 (0.3)				
DRAWN BY MC					REVIEW DRAWING NUMBERS				
DATE 05-10-07					DRAWING FILENAME M02779BJ_DC_00A.prt				
CHK'D					SCALE NONE				
					PART NO. SEE TABLE				
					DRAWING NO. 02779-16 (SHT. 2 of 2)				
					SIZE A				