Features



KUP93 series

General Purpose 3 to 10 Amp, Multicontact AC or DC Relay

A File E22575

File LR15734

Users should thoroughly review the technical data before selecting a product part number. It is recommended that users also seek out the pertinent approvals files of the agencies/laboratories and review them to ensure the product meets the requirements for a given application.

Coil Data

	Nominal Voltage	DC Resistance in Ohms ± 10%*	Must Operate Voltage	Nominal Coil Current (mA)
DC Coils	12 24	120 472	9.0 18.0	100 51
AC Coils	24 120 240	72 1,700 7,200	20.4 102.0 204.0	115 24 12

*AC coils, ± 15%

Contact Data @ 25°C

Contact arrangement to 3PDT.
Sockets available for all models.
Accepted pin pattern for HVAC industry.
Primarily designed for the HVAC industry.

Material: Fine silver or silver-cadmium oxide.

• AC coils 24, 120 & 240V 50/60 Hz.; DC 12 & 24VDC.

Contact Ratings

Material	UL/CSA Ratings	Life Expected
Fine silver	5A @ 28VDC or 240VAC, 80% PF, 1/10 HP @ 120VAC, 1/4 HP @ 240VAC	100,000
Silver- cadmium	10A @ 28VDC or 240VAC, 80% PF, 1/4 HP @ 120VAC,1/3 HP @ 240VAC	100,000
oxide	10 FLA, 30 LRA @ 120VAC, 5 FLA,15 LRA @ 240VAC	30,000

Operate Data @ 25°C

Must Operate Voltage:

DC Coils: 75% of nominal voltage or less. **AC Coils:** 85% of nominal voltage or less.

Operate Time (Excluding Bounce): 15 milliseconds, typical, at nominal voltage.

Release Time (Excluding Bounce):

DC Coils: 10 milliseconds, typical, at nominal voltage. **AC Coils:** 10 milliseconds, typical, at nominal voltage.

Environmental Data

- **Temperature Range:**
- Storage: All Coils: -45°C to +105°C. Operating: DC Coils: -45°C to +70°C.

AC Coils: -45°C to +45°C.

Initial Dielectric Strength

Between Open Contacts: 500V rms. Between Adjacent Contacts: 1,500V rms. Between Contacts and Coil: 1,500V rms.

Coil Data @ 25°C

Nominal Power: DC Coils: 1.2 Watts. AC Coils: 2.7VA. Initial Insulation Resistance: 100 megohms, min., at 25°C.

Mechanical Data

Termination: .187" x .020" quick connect. Enclosures: Clear polycarbonate dust cover. Weight: 3.0 oz. (86g) approximately.

Dimensions are shown for Dimension reference purposes only. Downloaded from <u>Elcodis.com</u> electronic components distributor

Dimensions are in inches over (millimeters) unless otherwise specified. Specifications and availability subject to change.

tyco Electronics


P	R	R
-	CX.	-

	-	

Our authorized distributors are more likely to stock the following items for immediate delivery.

No items in this series typically are stocked.


Outline Dimensions



Wiring Diagrams 3 Form C



KUP93 Sockets




KUP93 Socket Number

Socket	P C Socket With		
Color	Terminals		
Natural Nylon	27E168**		

**UL Recognized, file E22575

Socket: Rated 10 amperes. Will accept .187" (4.75mm) quick-connect terminals of all KUP93 relays.

Socket PC Board Layout (Component Side of Board)



Specifications and availability subject to change.