

## INT-A-PAK "Half-Bridge" (Ultrafast Speed IGBT), 108 A


**INT-A-PAK**
**FEATURES**

- Generation 5 Non Punch Through (NPT) technology
- Ultrafast: Optimized for hard switching speed 8 kHz to 60 kHz
- Low  $V_{CE(on)}$
- 10  $\mu$ s short circuit capability
- Square RBSOA
- Positive  $V_{CE(on)}$  temperature coefficient
- HEXFRED<sup>®</sup> antiparallel diode with ultrasoft reverse recovery characteristics
- Industry standard package
- $Al_2O_3$  DBC
- UL approved file E78996
- Compliant to RoHS directive 2002/95/EC
- Designed for industrial level


**RoHS  
COMPLIANT**
**PRODUCT SUMMARY**

$V_{CES}$	600 V
$I_C$ DC	108 A
$V_{CE(on)}$ at 100 A, 25 °C	2.6 V

**BENEFITS**

- Benchmark efficiency for UPS and welding application
- Rugged transient performance
- Direct mounting on heatsink
- Very low junction to case thermal resistance





**ABSOLUTE MAXIMUM RATINGS**

PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS
Collector to emitter voltage	$V_{CES}$		600	V
Continuous collector current	$I_C$	$T_C = 25\text{ °C}$	108	A
		$T_C = 80\text{ °C}$	74	
Pulsed collector current	$I_{CM}$		200	
Clamped inductive load current	$I_{LM}$		200	
Diode continuous forward current	$I_F$	$T_C = 25\text{ °C}$	106	
		$T_C = 80\text{ °C}$	69	
Gate to emitter voltage	$V_{GE}$		$\pm 20$	V
Maximum power dissipation	$P_D$	$T_C = 25\text{ °C}$	390	W
		$T_C = 80\text{ °C}$	219	
Isolation voltage	$V_{ISOL}$	Any terminal to case, $t = 1\text{ min}$	2500	V

<b>ELECTRICAL SPECIFICATIONS</b> ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Collector to emitter breakdown voltage	$V_{BR(CE)}$	$V_{GE} = 0\text{ V}, I_C = 500\text{ }\mu\text{A}$	600	-	-	V
Collector to emitter voltage	$V_{CE(on)}$	$V_{GE} = 15\text{ V}, I_C = 50\text{ A}$	-	1.95	2.1	
		$V_{GE} = 15\text{ V}, I_C = 100\text{ A}$	-	2.6	2.85	
		$V_{GE} = 15\text{ V}, I_C = 50\text{ A}, T_J = 125\text{ }^\circ\text{C}$	-	2.21	2.44	
		$V_{GE} = 15\text{ V}, I_C = 100\text{ A}, T_J = 125\text{ }^\circ\text{C}$	-	3.05	3.38	
Gate threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}, I_C = 500\text{ }\mu\text{A}$	3	4.6	6	
Collector to emitter leakage current	$I_{CES}$	$V_{GE} = 0\text{ V}, V_{CE} = 600\text{ V}$	-	0.01	0.1	mA
		$V_{GE} = 0\text{ V}, V_{CE} = 600\text{ V}, T_J = 150\text{ }^\circ\text{C}$	-	3.7	10	
Diode forward voltage drop	$V_{FM}$	$I_C = 50\text{ A}$	-	1.35	1.66	V
		$I_C = 100\text{ A}$	-	1.57	1.96	
		$I_C = 50\text{ A}, T_J = 125\text{ }^\circ\text{C}$	-	1.27	1.50	
		$I_C = 100\text{ A}, T_J = 125\text{ }^\circ\text{C}$	-	1.57	1.89	
Gate to emitter leakage current	$I_{GES}$	$V_{GE} = \pm 20\text{ V}$	-	-	$\pm 200$	nA

<b>SWITCHING CHARACTERISTICS</b> ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Turn-on switching loss	$E_{on}$	$I_C = 100\text{ A}, V_{CC} = 360\text{ V}, V_{GE} = 15\text{ V}, R_g = 4.7\text{ }\Omega, L = 200\text{ }\mu\text{H}, T_J = 25\text{ }^\circ\text{C}$	-	0.6	-	mJ
Turn-off switching loss	$E_{off}$		-	1.1	-	
Total switching loss	$E_{tot}$		-	1.7	-	
Turn-on switching loss	$E_{on}$	$I_C = 100\text{ A}, V_{CC} = 360\text{ V}, V_{GE} = 15\text{ V}, R_g = 4.7\text{ }\Omega, L = 200\text{ }\mu\text{H}, T_J = 125\text{ }^\circ\text{C}$	-	0.8	-	ns
Turn-off switching loss	$E_{off}$		-	1.3	-	
Total switching loss	$E_{tot}$		-	2.1	-	
Turn-on delay time	$t_{d(on)}$		-	197	-	
Rise time	$t_r$		-	50	-	
Turn-off delay time	$t_{d(off)}$		-	225	-	
Fall time	$t_f$	-	72	-		
Reverse bias safe operating area	RBSOA	$T_J = 150\text{ }^\circ\text{C}, I_C = 200\text{ A}, R_g = 27\text{ }\Omega, V_{GE} = 15\text{ V to }0$	Fullsquare			
Short circuit safe operating area	SCSOA	$T_J = 150\text{ }^\circ\text{C}, V_{CC} = 400\text{ V}, V_P = 600\text{ V}, R_g = 27\text{ }\Omega, V_{GE} = 15\text{ V to }0$	10	-	-	
Diode reverse recovery time	$t_{rr}$	$I_F = 50\text{ A}, dI_F/dt = 200\text{ A}/\mu\text{s}, V_{CC} = 400\text{ V}, T_J = 25\text{ }^\circ\text{C}$	-	116	140	ns
Diode peak reverse current	$I_{rr}$		-	11	15	A
Diode recovery charge	$Q_{rr}$		-	600	1050	nC
Diode reverse recovery time	$t_{rr}$	$I_F = 50\text{ A}, dI_F/dt = 200\text{ A}/\mu\text{s}, V_{CC} = 400\text{ V}, T_J = 125\text{ }^\circ\text{C}$	-	152	190	ns
Diode peak reverse current	$I_{rr}$		-	16	20	A
Diode recovery charge	$Q_{rr}$		-	1215	1900	nC

THERMAL AND MECHANICAL SPECIFICATIONS					
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS
Operating junction and storage temperature range	$T_J, T_{Stg}$	- 40	-	150	°C
Junction to case per leg	IGBT	-	0.23	0.32	°C/W
	Diode	-	0.38	0.64	
Case to sink per module	$R_{thCS}$	-	0.1	-	
Mounting torque	case to heatsink	-	-	4	Nm
	case to terminal 1, 2, 3	-	-	3	
Weight		-	185	-	g


 Fig. 1 - Typical IGBT Output Characteristics  
 $T_J = 25^\circ\text{C}$ ,  $t_p = 500 \mu\text{s}$ 

 Fig. 3 - Typical Transfer Characteristics  
 $V_{CE} = 20 \text{ V}$ ,  $t_p = 500 \mu\text{s}$ 

 Fig. 2 - Typical IGBT Output Characteristics  
 $T_J = 125^\circ\text{C}$ ,  $t_p = 500 \mu\text{s}$ 

 Fig. 4 - Typical Collector to Emitter Voltage vs.  
 Junction Temperature,  
 $V_{GE} = 15 \text{ V}$ ,  $500 \mu\text{s}$  pulse width




Fig. 5 - Diode Forward Characteristics,  $t_p = 500 \mu s$




Fig. 8 - Typical Switching Time vs.  $I_C$   
 $T_J = 125^\circ C$ ,  $L = 200 \mu H$ ,  $V_{CC} = 360 V$ ,  
 $R_g = 4.7 \Omega$ ,  $V_{GE} = 15 V$




Fig. 6 - Maximum Collector Current vs. Case Temperature




Fig. 9 - Typical Energy Loss vs.  $R_g$   
 $T_J = 125^\circ C$ ,  $L = 200 \mu H$ ,  $V_{CC} = 360 V$ ,  
 $I_{CE} = 100 A$ ,  $V_{GE} = 15 V$




Fig. 7 - Typical Energy Loss vs.  $I_C$ ,  $T_J = 125^\circ C$ ,  
 $L = 200 \mu H$ ,  $V_{CC} = 360 V$ ,  $R_g = 4.7 \Omega$ ,  $V_{GE} = 15 V$




Fig. 10 - Typical Switching Time vs.  $R_g$   
 $T_J = 125^\circ C$ ,  $L = 200 \mu H$ ,  $V_{CC} = 360 V$ ,  
 $I_{CE} = 100 A$ ,  $V_{GE} = 15 V$




Fig. 11 - Typical Diode  $I_{rr}$  vs.  $I_F$ ,  
 $T_J = 125^\circ\text{C}$




Fig. 14 - Typical Switching Losses vs. Gate Resistance,  
 $T_J = 125^\circ\text{C}$ ,  $L = 200\ \mu\text{H}$ ,  $R_g = 10\ \Omega$ ,  
 $V_{CC} = 360\ \text{V}$ ,  $V_{GE} = 15\ \text{V}$




Fig. 12 - Typical Diode  $I_{rr}$  vs.  $R_g$ ,  
 $T_J = 125^\circ\text{C}$ ,  $I_F = 100\ \text{A}$




Fig. 15 - Typical Switching Losses vs. Junction Temperature,  
 $L = 200\ \mu\text{H}$ ,  $R_g = 10\ \Omega$ ,  $V_{CC} = 360\ \text{V}$ ,  $V_{GE} = 15\ \text{V}$




Fig. 13 - Typical Diode  $I_{rr}$  vs.  $di_F/dt$ ,  
 $T_J = 125^\circ\text{C}$ ,  $V_{CC} = 360\ \text{V}$ ,  $I_F = 150\ \text{A}$ ,  $V_{GE} = 15\ \text{V}$




Fig. 16 - Typical Switching Losses vs.  
 Collector to Emitter Current,  
 $T_J = 125^\circ\text{C}$ ,  $R_{g1} = 4.7\ \Omega$ ,  $R_{g2} = 0\ \Omega$ ,  $V_{CC} = 360\ \text{V}$ ,  $V_{GE} = 15\ \text{V}$




Fig. 17 - Maximum Transient Thermal Impedance, Junction to Case (IGBT)





Fig. 18 - Maximum Transient Thermal Impedance, Junction to Case (HEXFRED®)

**ORDERING INFORMATION TABLE**

Device code	<b>G</b>	<b>B</b>	<b>100</b>	<b>T</b>	<b>S</b>	<b>60</b>	<b>N</b>	<b>PbF</b>
	①	②	③	④	⑤	⑥	⑦	⑧

- 1** - Insulated Gate Bipolar Transistor (IGBT)
- 2** - B = IGBT Generation 5 NPT
- 3** - Current rating (100 = 100 A)
- 4** - Circuit configuration (T = Half-bridge)
- 5** - Package indicator (S = INT-A-PAK)
- 6** - Voltage rating (60 = 600 V)
- 7** - Speed/type (N = Ultrafast IGBT)
- 8** - Lead (Pb)-free

**CIRCUIT CONFIGURATION**

**LINKS TO RELATED DOCUMENTS**

Dimensions	<a href="http://www.vishay.com/doc?95173">www.vishay.com/doc?95173</a>
------------	--



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.