

**Shielded Cable Clamps (Continued)**

**Crimp and Split-Ring Ferrules**

Shell Size	Cable Dia. (Max.)	← When using these Shield Kits →				← Use these Ferrules →				
		Straight Exit Shield Kit No.		90° Exit Die Cast Shield Kit No.		Split-Ring* Ferrule No.	Crimp Ferrule No. and Tooling No.**			
		Die Cast	Metal-Plated Plastic	With Slide Latch	Without Slide Latch		Inner	Outer	Die Set For Hand Tool 543344-1	Applicator Die Set
1	.200 5.08	745171-2	745854-5	—	—	745508-2	—	—	—	—
	.240 6.10	745171-5	745854-1	—	—	—	1-745129-8	745130-8	543013-2	813809-1
	.250 6.35	745171-1	745854-3	—	—	745508-3	—	—	—	—
	.280 7.11	745171-5	745854-1	—	—	—	3-745129-4	1-745130-6	1-543013-7	813809-7
	.370 9.40	745171-5	745854-1	—	—	745508-6	1-745129-7	1-745130-0	543013-6	813809-5
	.225 5.72	745172-3	747099-7	745652-4	—	745508-3	—	—	—	—
	.240 6.10	745172-1	747099-3	745652-2	745918-2	—	1-745129-8	745130-8	543013-2	813809-1
	.240 6.10	1-745172-3 745919-1	747099-1	745652-1	—	—	2-745129-1	745130-8	543013-3	813809-1
	.280 7.11	1-745172-3 745919-1	747099-1	745652-1	—	—	3-745129-2	1-745130-6	1-543013-6	813809-7
	.300 7.62	745172-2 745919-3	747099-5	745652-3	745918-3	745508-4	—	—	—	—
2	.350 8.90	1-745172-3 745919-1	747099-1	745652-1	—	—	2-745129-0	745130-9	543013-4	813809-2
	.365 9.27	745172-1	747099-3	745652-2	745918-2	—	1-745129-7	1-745130-0	543013-6	813809-5
	.375 9.53	745172-1 745919-2	747099-3	745652-2	745918-2	745508-6	—	—	—	—
	.430 10.92	1-745172-3 745919-1	747099-1	745652-1	—	745508-1	1-745129-9	1-745130-1	543013-7	813809-3
	.240 6.10	745173-3	745833-5	745653-3	747194-3	—	2-745129-1	745130-8	543013-3	813809-1
	.280 7.11	745173-5	745833-9	745653-5	—	745508-4	—	—	—	—
	.280 7.11	745173-3	745833-5	745653-3	747194-3	—	3-745129-2	1-745130-6	1-543013-6	813809-7
	.350 8.90	745173-4	745833-7	745653-4	—	745508-5	—	—	—	—
	.350 8.90	745173-3	745833-5	745653-3	747194-3	—	2-745129-0	745130-9	543013-4	813809-2
	.430 10.92	745173-3	745833-5	745653-3	747194-3	745508-1	1-745129-9	1-745130-1	543013-7	813809-3
3	.430 10.92	745173-1	745833-1	745653-1	—	—	2-745129-3	1-745130-1	543013-8	813809-3
	.480 12.19	745173-2	745833-3	745653-2	—	745508-8	—	—	—	—
	.530 13.46	745173-1	745833-1	745653-1	—	745508-9	2-745129-2	1-745130-2	1-543013-0	813809-4

Cable Connectors

\*For split-ring ferrules, Min. O.D. is .040 [1.02] smaller than Max. O.D.

\*\*For inner and outer ferrules, Min. O.D. is .050 [1.27] smaller than Max. O.D. At the Max. cable O.D. the Min. insulation thickness is .060 [1.52].

Continued on Page 150