


9808	9101	5650	8679
<p>9808-0-15-XX-16-XX-04-0 Press-fit in 1,70 mounting hole</p>	<p>9101-0-15-XX-16-XX-10-0 Press-fit in 1,70 mounting hole</p>	<p>5650-0-19-XX-16-XX-10-0 Press-fit in 1,70 mounting hole</p>	<p>8679-0-15-XX-16-XX-10-0 Solder mount in 1,80 min. mounting hole</p>

8827	6021	1873
<p>8827-0-15-XX-16-XX-04-0 Press-fit in 1,55 mounting hole</p>	<p>6021-0-15-XX-16-XX-10-0 Solder mount in 1,57 min. mounting hole</p>	<p>1873-0-15-XX-16-XX-04-0 Press-fit in 1,68 mounting hole</p>



<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY</p> <p>TOLERANCES ON: LENGTHS: ± 0,13 DIAMETERS: ± 0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 15 - XX - 16 - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <p>01 5,08µm TIN/LEAD OVER NICKEL</p> <p>80 5,08µm TIN OVER NICKEL ◇</p> <p>15 0,25µm GOLD OVER NICKEL ◇</p> <p>CONTACT</p> <p>#16 CONTACT (DATA ON PAGE 210)</p>	<p>SPECIFY CONTACT FINISH:</p> <p>01 2,54µm TIN/LEAD OVER NICKEL</p> <p>80 2,54µm TIN OVER NICKEL ◇</p> <p>27 0,76µm GOLD OVER NICKEL ◇</p>
--	---	---

