| REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK, DIV. OF TEKTEST INC. MAXIMUM RATINGS ARE NOT TO BE USED CONCURRENTLY. | THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK. THE INFORMATION IS NOT TO BE MAXIMUM TESTED RATINGS IN A HANDS-FREE CONTROLLED ENVIRONMENT. | THE INFORMATION CONTAINED IN THIS DOCUME MAXIMU   |
|--|--|---|
| SCALE 1:1 SHEET 1 OF 1   | DO NOT SCALE DRAWING   | APPLICATION   |
| 08505 9110   | SEE NOTE.  | NEXT ASSY USED ON   |
| SIZE   CODE IDENT NO.   DRAWING NO.   REV  |  |   |
|  |  |   |
| TOLONG [C.64] V.C. V.C.F.E   |  |   |
| L. 10/10 DESCRIPTION   | ± .XX± ± DRAWN   |   |
| DATE DATE DIVISION OF TEXTEST INC. ARCADIA, CA 91006 U.S.A.  | TOLERANCES ARE: FRACTIONS DECIMALS ANGLES APPROVALS  |   |
| 171500   | UNLESS OTHERWISE SPECIFIED CONTRACT NO. DIMENSIONS ARE IN INCHES   |   |
|  |  |   |
| ,  |  |   |
|  |  | <del></del>   |
|  |  |   |
|  |  |   |
|  |  |   |
|  | CURRENT: 2.5 AMPS VOLTAGE: 1000 (300 UL) W.V.D.C. TEMPERATURE: 221°F (105°C)   | MAXIMUM CURRENT: 2.5 , MAXIMUM VOLTAGE: 1000 MAXIMUM TEMPERATURE:                                       |
|  |  |   |
|  | )PPER<br>NSULATION<br>S.   | 2. P/N: W-200/COLOR 22AWG 65X40 TINNED COPPER 0.070 [1.78] O.D. PVC INSULATION AVAILABLE IN TEN COLORS. |
|  | CONTACT: BeCu OR PHOSPHOR BRONZE, 40μ [1.02μm] MIN<br>GOLD OVER NICKEL PLATED.   | CONTACT: BeCu OR PHOS   |
|  | um] MIN GOLD OVER NICKEL   | BODY: BRASS, 40µ [1.02<br>PLATED.   |
|  | MOLDED NYLON. AVAILABLE IN BLACK.  | 1. P/N: 9205—HS<br>HEAT SHRINK: MOLDED N  |
| DESCRIPTION DATE APPROVED  | PECIFIED LER   | NOTES: UNLESS OTHERWISE SPECIFIED   |
| REVISIONS  |  |   |