THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK, THE INFORMATION IS NOT TO BE REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK, DIV. OF TEKTEST INC.	NT IS PROPRIETARY TO E-Z-HOOK. THE WITESTED RATINGS IN A HANDS-FREE C	THE INFORMATION CONTAINED IN THIS DOCUME MAXIMULE.
	DO NOT SCALE DRAWING	APPLICATION
A 08505 9169	-SEE NOTE.	NEXT ASSY USED ON
SIZE CODE IDENT NO. DRAWING NO. REVE	FINISH	
SIX SID BAN PLUG (9203)	OEE NOIE.	
L 10/10 DESCRIPTION L 10/10 DESCRIPTION	. XXX + +	
APPROVALS DATE APPROVALS DATE APPROVALS DATE	FRACTIONS DECIMALS ANGLES	
	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
0.175 [4.45]	0.175	
0.735 [18.67]	0.7	
1.610 [40.89]	AMPS (300 UL) W.V.D.C. 221°F (105°C)	4. PERFORMANCE MAXIMUM CURRENT: 2.5 AMPS MAXIMUM VOLTAGE: 1000 (300 UL) W.V.D.C. MAXIMUM TEMPERATURE: 221°F (105°C)
)PPER NSULATION S.	3. P/N: W-200/COLOR 22AWG 65X40 TINNED COPPER 0.070 [1.78] O.D. PVC INSULATION AVAILABLE IN TEN COLORS.
RS.	º/N: 9203COLOR HOUSING: MOLDED NYLON. AVAILABLE IN TEN COLORS. FRAME: BRASS. NICKEL PLATED. CONTACT: BeCu OR PHOSPHOR BRONZE. NICKEL PLATED.	2. P/N: 9203COLOR HOUSING: MOLDED NYLON FRAME: BRASS. NICKEL P CONTACT: BeCu OR PHOS
2µm]	CONTACT: BeCu OR PHOSPHOR BRONZE. 40µ [1.02µm] MIN GOLD OVER NICKEL PLATED.	CONTACT: BeCu OR PHOS MIN GOLD OVEF
	'/N: 9205—HS INSULATOR: HEAT SHRINK TUBING 221. BLACK. BODY: BRASS. 40µ [1.02µm] MIN GOLD OVER NICKEL	1. P/N: 9205—HS INSULATOR: HEAT SHRINK TUBING BODY: BRASS. 40µ [1.02µm] MIN
LTR DESCRIPTION REVISIONS APPROVED	PECIFIED	NOTES: UNLESS OTHERWISE SPECIFIED