



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

RB751S-40LP

Features

- Small surface mounting type
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Marking: 5

- 5 - +


Maximum Ratings


Symbol	Rating	Rating	Unit
V_{RM}	Peak Reverse Voltage	40	V
V_R	DC Reverse Voltage	30	V
Ιο	Mean Rectifying Current	30	mA
I _{FSM}	Peak Forward Surge Current*	150	mA
T_J	Junction Temperature	125	$^{\circ}\mathbb{C}$
T _{STG}	Storage Temperature	-40 to +125	$^{\circ}\mathbb{C}$

Electrical Characteristics @ 25°C Unless Otherwise Specified

L	oyoc.	i didiliotoi		.,,,,	max	Oilito
	V_{F}	Forward Voltage (I _F =1mAdc)			0.37	Vdc
	I_R	Reverse Current (V _R =30Vdc)			0.5	uAdc

30 mA Schottky Rectifier 40 Volts






		DIME	NSIONS		
DIM	INC	HES	M	MM	
DIM	MIN	MAX	MIN	MAX	NOTE
A	0.018	0.022	0.45	0.55	
В	0.000	0.003	0.01	0.07	
С	0.018	REF.	0.450	REF.	
D	0.037	0.041	0.95	1.05	
Е	0.022	0.026	0.55	0.65	
F	0.016 REF.		0.400 REF.		
G	0.011	0.013	0.275	0.325	
Н	0.000 REF.		0.010 REF.		
Ť	0.011	0.012	0.275	0.225	



Typical Characteristics

●Electrical characteristic curves (Ta = 25°C)



Ta = 125 °C

Ta = 75 °C

Typ.

Typ.

pulse measurement

To = 105 °C

Typ.

pulse measurement

To = 105 °C

Typ.

pulse measurement

To = 105 °C

Typ.

pulse measurement

Typ.

Typ.

Pulse measurement

Typ.




Fig. 1 Forward characteristics

Fig. 2 Reverse characteristics

Fig. 3 Capacitance between terminals characteristics



Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 5Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.