


International
IOR Rectifier

122NQ030PbF

SCHOTTKY RECTIFIER

120Amp



Major Ratings and Characteristics

Characteristics	Values	Units
$I_{F(AV)}$ Rectangular waveform	120	A
V_{RRM}	30	V
I_{FSM} @ $t_p = 5 \mu s$ sine	18000	A
V_F @ 120Apk, $T_J = 125^\circ C$	0,47	V
T_J range	-55 to 150	$^\circ C$

Description/ Features

The 122NQ.. high current Schottky rectifier module series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 150 °C junction temperature. Typical applications are in high current switching power supplies, plating power supplies, UPS systems, converters, free-wheeling diodes, welding, and reverse battery protection.

- 150 °C T_J operation
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Lead-Free

Case Styles



HALF-PAK (D-67)

Voltage Ratings

Part number	122NQ030PbF
V_R Max DC Reverse Voltage (V)	30
V_{RM} Max Working Peak Reverse Voltage (V)	

Absolute Maximum Ratings

Parameters	122NQ	Units	Conditions
$I_{F(AV)}$ Max Average Forward Current *See Fig. 5	120	A	50% duty cycle @ $T_C = 115^\circ\text{C}$, rectangular wave form
I_{FSM} Max Peak One Cycle Non-Repetitive Surge Current *See Fig. 7	18000 2000	A	5 μs Sine or 3 μs Rect. pulse 10ms Sine or 6ms Rect. pulse Following any rated load condition and with rated V_{RM} applied
E_{AS} Non-Repetitive Avalanche Energy	54	mJ	$T_J = 25^\circ\text{C}$, $I_{AS} = 11$ Amps, $L = 1$ mH
I_{AR} Repetitive Avalanche Current	12	A	Current decaying linearly to zero in 1 μsec Frequency limited by T_J , max $V_A = 1.5 V_R$ typical

Electrical Specifications

Parameters	122NQ	Units	Conditions
V_{FM} Max Forward Voltage Drop (Per Leg) *See Fig. 1 (1)	0.57	V	@ 120A $T_J = 25^\circ\text{C}$
	0.75	V	@ 240A
	0.47	V	@ 120A $T_J = 125^\circ\text{C}$
	0.67	V	@ 240A
I_{RM} Max Reverse Leakage Current (Per Leg) *See Fig. 2 (1)	10	mA	$T_J = 25^\circ\text{C}$ $V_R = \text{rated } V_R$
	560	mA	$T_J = 125^\circ\text{C}$
C_T Max Junction Capacitance	7400	pF	$V_R = 5V_{DC}$ (test signal range 100Khz to 1Mhz) 25°C
L_S Typical Series Inductance	7.0	nH	From top of terminal hole to mounting plane
dv/dt Max Voltage Rate of Change (Rated V_R)	10000	V/ μs	

(1) Pulse width 300 μs , Duty Cycle 2%

Thermal-Mechanical Specifications

Parameters	122NQ	Units	Conditions	
T_J Max Junction Temperature Range	-55 to 150	$^\circ\text{C}$		
T_{stg} Max Storage Temperature Range	-55 to 150	$^\circ\text{C}$		
R_{thJC} Max Thermal Resistance Junction to Case	0.38	$^\circ\text{C/W}$	DC operation * See Fig. 4	
R_{thCS} Typical Thermal Resistance, Case to Heatsink	0.05	$^\circ\text{C/W}$	Mounting surface, smooth and greased	
wt Approximate Weight	30 (1.06)	g (oz.)		
T Mounting Torque	Min.	3 (26.5)	Non-lubricated threads	
	Max	4 (35.4)		
	Terminal Torque	Min.		3.4 (30)
		Max		5 (44.2)
Case Style	HALF PAK Module			




Fig. 1 - Max. Forward Voltage Drop Characteristics





Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics




Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Max. Non-Repetitive Surge Current





Fig. 8 - Unclamped Inductive Test Circuit

(2) Formula used: $T_c = T_j - (P_d + P_{d_{REV}}) \times R_{thJC}$
 $P_d = \text{Forward Power Loss} = I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$ (see Fig. 6);
 $P_{d_{REV}} = \text{Inverse Power Loss} = V_{R1} \times I_{R1} (1 - D)$; $I_{R1} @ V_{R1} = \text{rated } V_R$

Outline Table



Ordering Information Table

Device Code					
12	2	N	Q	030	PbF
(1)	(2)	(3)	(4)	(5)	(6)
1	-	Average Current Rating (x 10)			
2	-	Product Silicon Identification			
3	-	N = NOT Isolated			
4	-	Q = Schottky Rectifier Diode			
5	-	Voltage Rating (030 = 30V)			
6	-	Lead-Free			

122NQ030PbF

Bulletin PD-21141 05/06

International
IOR Rectifier

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level and Lead-Free.
Qualification Standards can be found on IOR's [web](#) site.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 9245, USA Tel:(310) 252-7105
TAC Fax(310) 252-7309
05/06

Document Number: 94128

www.vishay.com

6



Notice

The products described herein were acquired by Vishay Intertechnology, Inc., as part of its acquisition of International Rectifier's Power Control Systems (PCS) business, which closed in April 2007. Specifications of the products displayed herein are pending review by Vishay and are subject to the terms and conditions shown below.

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

International Rectifier®, IR®, the IR logo, HEXFET®, HEXSense®, HEXDIP®, DOL®, INTERO®, and POWIRTRAIN® are registered trademarks of International Rectifier Corporation in the U.S. and other countries. All other product names noted herein may be trademarks of their respective owners.