

Solutions for Electronic Specialty Markets (ESM)

[Product Catalog for Electronic Specialty Markets](#) [3M Fiber Optics](#) [Cable Assembly](#)  
[Connectors & Couplings](#) [Crimplok SC Connectors](#)

Product Catalog for Electronic Specialty Markets

- 3M Electronic Specialty Markets New Product Releases
- 3M Abrasives
- 3M Adhesives, Cleaners & Compounds
- 3M Breadboards & Test Clips
- 3M Cable & Assemblies
- 3M Copper Interconnects
- 3M Fiber Optics**
- 3M Fire Protection
- 3M Heat Shrink
- 3M Identification Systems
- 3M Occupational Health & Safety Products
- 3M Protective Bumpers
- 3M Reclosable Fasteners
- 3M Splicing, Terminating & Ducting
- 3M Static Control
- 3M Tapes
- 3M Terminals, Kits & Tools
- 3M Vacuums & Accessories
- 3M Warehousing & Packaging Supplies
- 3M Wire Connectors

## 3M SC MM BEIGE BOOT CONNECTOR 6306-BE

[Printer-friendly format](#)



The SC Connector is designed for the most advanced fiber optic systems requiring exceptional stability, low reflections (single - mode) and high density.

[\[click to enlarge\]](#)

GTIN(UPC/EAN) : 0 00 54007 91724 3  
 3M Id : 80 - 6107 - 6501 - 0

### Additional Information

The SC Connector is available in single - mode and multimode utilizing epoxy adhesive. It is also available in multimode preloaded with Hot Melt adhesive, enabling a field termination in less than two minutes for multiple terminations. The SC Connector is also available as the Crimplok Connector. The Crimplok Connector combines the speed of non - adhesive connectors with the performance


[Full Text . . .](#)

### Learn More . . .

- [Packaging Data](#)
- [SC & FC/PC3 Pull - Proof Fiber Optic Connectors - Instructions/Manual \(PDF 729.2 K\)](#)
- [SC Connector - Illustration/Line Art \(EPS 1.5 MB\)](#)
- [SC Connector - Illustration/Line Art \(EPS 921.0 K\)](#)
- [SC&FC/PC3 Pull - Proof Fiber Optic Connectors - Instructions/Manual \(PDF 205.6 K\)](#)
- [SC\\_FC3 Epoxy Connectors - Instructions/Manual \(PDF 11.2 K\)](#)

#### Please Note:

Adobe® Acrobat® Reader is required to view PDF documents.



### Other Tools

- What's New
- Sales Contacts
- U.S. Distributors

### Search This Product Catalog

By Keyword

### Characteristics

<b>Boot Material</b>	Polyester
<b>China RoHS - Below MCV</b>	Yes
<b>EU RoHS Compliant</b>	Yes
<b>Flame Retardant</b>	UL-94 V-O
<b>Operating Temperature Range</b>	-40 to 85 Degree Celsius
<b>Storage Temperature</b>	-40 to 85 Degree Celsius