

This document was generated on 02/01/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0190070021
Status: Active

Description: Flag InsulKrimp™ Quick Disconnect, Female, for 14-16 (2.00-1.30) Wire, Box, Tab

6.35mm (.250") x 0.81mm (.032")

Documents:

Drawing (PDF) Product Specification PS-19902-013 (PDF) RoHS Certificate of Compliance (PDF)

Agency Certification

CSA LR18689 UL E79133

General

Product Family Quick Disconnects

Type Quick Disconnect

Physical

Barrel Type Closed
Color - Resin Natural
Flammability 94V-2
Gender Female
Glow-Wire Compliant No
Insulation Nylon (PA)
Lock to Mating Part None

Insulation Nylon
Lock to Mating Part None
Material - Metal Brass
Material - Resin Nylon
Orientation Flag
Packaging Type Bag
Polarized to Mating Part No
Tab Thickness 0.81m

 Tab Thickness
 0.81mm (.032")

 Tab Width
 6.35mm (.250")

 Temperature Range - Operating
 -65°C to +105°C

 Wire Insulation Diameter
 5.08mm (.200") max.

 Wire Size AWG
 14, 16

 Wire Size mm²
 1.30 - 2.00

Electrical

Voltage - Maximum 600V

Material Info

Old Part Number BB-2221

Reference - Drawing Numbers

Product Specification PS-19902-008, PS-19902-013

Sales Drawing SD-19007-004

Series image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

<u>19007</u>Series

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

DescriptionProduct #Hand Crimp Tool0640014100Crimp Head for the0640054100AT-200™ Pneumatic

Hand Tool

This document was generated on 02/01/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION