

**PIDG Terminals** (Continued)**PIDG Ring Tongue Terminals** (Continued)**Material and Finish**

Insulation — Nylon

Terminal Body and Metallic

Sleeve — Copper per ASTM B-152,
tin plated per MIL-T-10727

Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Stud Size	Dim. W	Terminal Insulation Color	Wire Insulation Diameter Max.	Part Numbers Loose Piece
12-10 5,180-13,100 [2.62-6.64]	1.07 .042	6	7.14	Yellow	6.35 .250	35149*
		M3.5	.281			
		8	9.53	Yellow	6.35 .250	35108*
		M4	.375			
		10	9.53	Yellow	6.35 .250	35109*
			.375			
		1/4	13.49	Yellow	6.35 .250	35110*
		M6	.531			
15/16	13.49	Yellow	6.35 .250	35111*		
M8	.531					
3/8	15.06	Yellow	6.35 .250	35112*		
	.593					
1/2	19.05	Yellow	6.35 .250	35151*		
M12	.750					



*Available in small packaging quantities.

PIDG Spade Tongue Terminals**Material and Finish**

Insulation — Nylon

Terminal Body and Metallic

Sleeve — Copper per ASTM B-152,
tin plated per MIL-T-10727

Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Stud Size	Dim. W	Terminal Insulation Color	Wire Insulation Diameter Max.	Part Numbers Loose Piece
22-16 509-3,260 [0.26-1.65]	0.84 .033	2	4.62	Red	3.56 .140	328394*
		M2	.182			
		4	5.54	Red	3.56 .140	327717*
			.218			
		6	6.35	Red	3.56 .140	34541*
M3.5	.250					
8	9.53	Red	3.56 .140	32053*		
M4	.375					
10	9.53	Red	3.56 .140	32054*		
	.375					
16-14 2,050-5,180 [1.04-2.62]	0.84 .033	6	7.54	Blue	4.32 .170	35559*
		M3.5	.297			
		8	9.78	Blue	4.32 .170	32059*
M4	.385					
10	9.78	Blue	4.32 .170	32060*		
	.385					
12-10 5,180-13,100 [2.62-6.64]	1.07 .042	10	10.31	Yellow	5.84 .230	32589*



*Available in small packaging quantities.

Power

Terminals and Miscellaneous