

# PIDG Terminals

## PIDG Ring Tongue Terminals

### Material and Finish

Insulation Nylon

Terminal Body and Metallic

Sleeve — Copper per ASTM B-152,  
tin plated per MIL-T-10727

Wire Size Circular Mils [mm <sup>2</sup> ]	Tongue Material Thickness Max.	Stud Size	Dim. W	Terminal Insulation Color	Wire Insulation Diameter Max.	Part Numbers Loose Piece
26-22 202-810 [0.10-0.41]	0.51 .020	2 M2	3.56 .140	Yellow	2.08 .082	323912*
		4	5.16 .203	Yellow	2.08 .082	323914*
		6 M3.5	5.16 .203	Yellow	2.08 .082	323915*
		8 M4	6.35 .250	Yellow	2.08 .082	323916*
		10	6.35 .250	Yellow	2.08 .082	324075*
22-16 509-3,260 [0.26-1.65]	0.84 .033	2 M2	5.54 .218	Red	3.18 .125	328657*
		4	5.54 .218	Red	3.56 .140	31880*
		6 M3.5	7.14 .281	Red	3.56 .140	36152*
		8 M4	7.92 .312	Red	3.56 .140	31890*
		10	7.92 .312	Red	3.56 .140	36154*
		1/4 M6	11.91 .469	Red	3.56 .140	31894*
		5/16 M8	11.91 .469	Red	3.56 .140	31895*
		3/8	13.49 .531	Red	3.56 .140	31897*
16-14 2,050-5,180 [1.04-2.62]	0.84 .033	4	6.35 .250	Blue	4.32 1.70	328996*
		6 M3.5	6.35 .250	Blue	4.32 1.70	320619*
		8 M4	8.71 .343	Blue	4.32 1.70	320565*
		10	8.71 .343	Blue	4.32 1.70	36160*
		1/4 M6	11.91 .469	Blue	4.32 1.70	321045*
		5/16 M8	11.91 .469	Blue	4.32 1.70	328998*
16-14D <sup>1</sup> 2,050-5,180 [1.04-2.62]	1.27 .050	8 M4	8.71 .343	Yellow/Blk.	5.84 .230	320627*
		10	8.71 .343	Yellow/Blk.	5.84 .230	320630*



\*Available in small packaging quantities.

<sup>1</sup>Heavy duty for extra mechanical strength.