

Splices

Selection Information



PIDG Nylon Insulated with Insulation Grip

- Copper inner sleeve
- Vibration resistant
- Barrel serrations
- Nylon insulation



PLASTI-GRIP Vinyl Insulated

- Funnel ramp entry
- Barrel serrations or dimples
- Vinyl insulation



SOLISTRAND Uninsulated

- Bell mouth
- Brazed seam
- Barrel serrations or dimples

Butt Splices

| Wire Size | PIDG Nylon Insulated | PLASTI-GRIP Vinyl Insulated | SOLISTRAND Uninsulated |
|-----------|----------------------|-----------------------------|------------------------|
| 22-16 | 320559 | 34070 | 31818 |
| 16-14 | 320562 | 34071 | 31819 |
| 12-10 | 320570 | 34072 | 32151 |
| 8 | — | — | 34321 |
| 6 | — | — | 34322 |
| 4 | — | — | 34323 |
| 2 | — | — | 35189 |
| 1/0 | — | — | 36957 |
| 2/0 | — | — | 36958 |
| 3/0 | — | — | 36959 |
| 4/0 | — | — | 36960 |

Parallel Splices

| Wire Size | PIDG Nylon Insulated | PLASTI-GRIP Vinyl Insulated | SOLISTRAND Uninsulated |
|-----------|----------------------|-----------------------------|------------------------|
| 22-16 | — | — | 34130 |
| 16-14 | — | — | 34137 |
| 12-10 | — | — | 34138 |
| 8 | — | — | 34318 |
| 6 | — | — | 34319 |
| 4 | — | — | 34320 |
| 2 | — | — | 35187 |
| 1/0 | — | — | 36946 |
| 2/0 | — | — | 36948 |
| 3/0 | — | — | 36909 |
| 4/0 | — | — | 36951 |