

Ring Terminals

Selection Information



**PIDG Nylon Insulated with Insulation Grip**

- Copper inner sleeve
- Vibration resistant
- Barrel serrations
- Nylon insulation



**PLASTI-GRIP Vinyl Insulated**

- Funnel ramp entry
- Barrel serrations or dimples
- Vinyl insulation



**SOLISTRAND Uninsulated**

- Bell mouth
- Brazed seam
- Barrel serrations or dimples

| Wire Size | Stud Size   | PIDG Nylon Insulated | PLASTI-GRIP Vinyl Insulated | SOLISTRAND Uninsulated |
|-----------|-------------|----------------------|-----------------------------|------------------------|
| 22-16     | 6           | 53407-1              | 34142                       | 34107                  |
|           | 8           | 53408-1              | 34145                       | 34108                  |
|           | 10          | 36154                | 34146                       | 34112                  |
| 16-14     | 6           | 320619               | 34158                       | 321684                 |
|           | 8           | 320565               | 34160                       | 324955                 |
|           | 10          | 36160                | 34161                       | 34123                  |
| 12-10     | 8           | 53424-1              | 34853                       | 32994                  |
|           | 10          | 36161                | 34854                       | 33457                  |
|           | 1/4 [6.35]  | 320569               | 34855                       | 35772                  |
| 8         | 10          | —                    | 52263-1                     | 33460                  |
|           | 1/4 [6.35]  | —                    | 52041-3                     | 33461                  |
|           | 5/16 [7.94] | —                    | 52291                       | 33462                  |
|           | 3/8 [9.53]  | —                    | 52291-1                     | 33463                  |
|           | 1/2 [12.70] | —                    | 52262-1                     | 35664                  |
| 6         | 10          | —                    | 52265                       | 33464                  |
|           | 1/4 [6.35]  | —                    | 52042-3                     | —                      |
|           | 5/16 [7.94] | —                    | 52264-2                     | 33466                  |
|           | 3/8 [9.53]  | —                    | 52264-1                     | 33467                  |
|           | 1/2 [12.70] | —                    | 52350                       | 320344                 |
| 4         | 10          | —                    | 52043-2                     | 33468                  |
|           | 1/4 [6.35]  | —                    | 52043-3                     | 33469                  |
|           | 5/16 [7.94] | —                    | 52266-3                     | 33470                  |
|           | 3/8 [9.53]  | —                    | 52266-4                     | 33471                  |
|           | 1/2 [12.70] | —                    | —                           | 35668                  |
| 2         | 1/4 [6.35]  | —                    | 52267-1                     | 52267                  |
|           | 5/16 [7.94] | —                    | 52044-4                     | 322870                 |
|           | 3/8 [9.53]  | —                    | 52044-5                     | 321600                 |
|           | 1/2 [12.70] | —                    | —                           | 35185                  |
| 1/0       | 3/8 [9.53]  | —                    | —                           | 36917                  |
|           | 1/2 [12.70] | —                    | —                           | 36919                  |
| 2/0       | 3/8 [9.53]  | —                    | —                           | 321871                 |
|           | 1/2 [12.70] | —                    | —                           | 321873                 |
| 3/0       | 3/8 [9.53]  | —                    | —                           | 321875                 |
| 4/0       | 3/8 [9.53]  | —                    | —                           | 321878                 |
|           | 1/2 [12.70] | —                    | —                           | 321880                 |

4-3