



# PAN-TERM® TERMINALS Priced from \$43.06 per 100

Designed and manufactured for fast assembly and long, reliable performance.

- Funnel entry available on vinyl and nylon insulated terminals — to speed assembly
- All are made of electrolytically refined copper to provide the optimum combination of crimp forming properties and low resistance, high conductivity terminations
- Applicable Sizes Meet Mil. Spec. MIL-T-7928G, MS25036, MS20659, UL and/or CSA requirements
- PANDUIT has a wide assortment of manual, controlled cycle, pneumatic and battery operated hydraulic crimping tools which gives you reliable connections at a lower installed cost

## RINGS



**NYLON — INSULATION GRIP SLEEVE**




**NON-INSULATED —BRAZED SEAM**



**MULTIPLE STUD— VINYL INS. FUNNEL ENTRY**



**MULTIPLE STUD— NYLON INS. INSULATION GRIP SLEEVE**



**Tubular Ring Terminal**

Stud Size	Wire Size — AWG			
	26-22	22-18	16-14	12-10
<b>NYLON INS.—FUNNEL ENTRY GRIP SLEEVE</b>				
#4		PNF18-4R-C	PNF14-4R-C	PNF10-6R-L
#6		PNF18-6R-C	PNF14-6R-C	
#6 NARROW		PNF18-6RN-C	PNF14-6RN-C	
#8		PNF18-8R-C	PNF14-8R-C	PNF10-8R-L
#10		PNF18-10R-C	PNF14-10R-C	PNF10-10R-L
1/4"		PNF18-14R-C	PNF14-14R-C	PNF10-14R-L
5/16"		PNF18-56R-C	PNF14-56R-C	PNF10-56R-L
3/8"		PNF18-38R-C	PNF14-38R-L	PNF10-38R-L
<b>NYLON INS.—INSULATION GRIP SLEEVE</b>				
#2	PN22-2R-C	PN18-4R-C	PN14-4R-C	
#4	PN22-4R-C	PN18-4RN-C	PN14-4RN-C	
#4 NARROW		PN18-6R-C	PN14-6R-C	PN10-6R-L
#6	PN22-6R-C	PN18-6RN-C	PN14-6RN-C	
#6 NARROW		PN18-8R-C	PN14-8R-C	PN10-8R-L
#8	PN22-8R-C	PN18-10R-C	PN14-10R-C	PN10-10R-L
#10	PN22-10R-C	PN18-14R-C	PN14-14R-C	PN10-14R-L
1/4"		PN18-56R-C	PN14-56R-C	PN10-56R-L
5/16"		PN18-38R-C	PN14-38R-L	PN10-38R-L
3/8"				
<b>NYLON INS.—MULTIPLE STUD SIZE</b>				
#6, #8, #10		PN18-610R-C	PN14-610R-C	PN10-610R-L
<b>NYLON INS.—EXPANDED (RX) INSULATION</b>				
#4			PN14-4RX-C	PN10-6RX-L
#6			PN14-6RX-C	PN10-8RX-L
#8			PN14-8RX-C	PN10-10RX-L
#10			PN14-10RX-C	PN10-14RX-L
1/4"			PN14-14RX-C	PN10-14RX-L
5/16"			PN14-56RX-C	PN10-56RX-L
3/8"			PN14-38RX-L	PN10-38RX-L
<b>VINYL INS.—FUNNEL ENTRY (#22-10)</b>				
#2	PV22-2R-C	PV18-4R-C	PV14-4R-C	
#4	PV22-4R-C	PV18-6R-C	PV14-6R-C	PV10-6R-L
#6	PV22-6R-C	PV18-6R-C	PV14-6R-C	
#6 NARROW		PV18-8R-C	PV14-8R-C	PV10-8R-L
#8	PV22-8R-C	PV18-10R-C	PV14-10R-C	PV10-10R-L
#10	PV22-10R-C	PV18-14R-C	PV14-14R-C	PV10-14R-L
1/4"		PV18-56R-C	PV14-56R-C	PV10-56R-L
5/16"		PV18-38R-C	PV14-38R-L	PV10-38R-L
3/8"				
<b>VINYL INS.—MULTIPLE STUD SIZE</b>				
#6, #8, #10		PV18-610R-C	PV14-610R-C	PV10-610R-L
<b>VINYL INS.—EXPANDED INSULATION (RX)</b>				
#4		PV18-4RX-C	PV14-4RX-C	PV10-6RX-L
#6		PV18-6RX-C	PV14-6RX-C	PV10-8RX-L
#8		PV18-8RX-C	PV14-8RX-C	PV10-10RX-L
#10		PV18-10RX-C	PV14-10RX-C	PV10-14RX-L
1/4"		PV18-14RX-C	PV14-14RX-C	PV10-14RX-L
5/16"		PV18-56RX-C	PV14-56RX-C	PV10-56RX-L
3/8"		PV18-38RX-C	PV14-38RX-L	PV10-38RX-L

Stud Size	Wire Size — AWG <sup>2</sup>				
	6	2	1/0	3/0	250
#10	S6-10R-E	S2-10R-X	S1/0-14R-X	S3/0-14R-5	
1/4"	S6-14R-E	S2-14R-X	S1/0-56R-X	S3/0-56R-5	S250-56R-5
5/16"	S6-56R-E	S2-56R-X	S1/0-38R-X	S3/0-38R-5	S250-38R-5
3/8"	S6-38R-E	S2-38R-X		S3/0-76R-5	S250-76R-5
7/16"					
1/2"		S2-12R-X	S1/0-12R-X	S3/0-12R-5	S250-12R-5

<sup>1</sup> Call AA Electric for installation tooling for Tubular Ring terminals.

<sup>2</sup> Wire Size - AWG 8, 4, 2/0, and 4/0 also available - contact AA Electric.

\* Reg. trademark Elf Atochem North America

Part No. shown for Std. Pkg. Qty. For Bulk Pkg. (unless already shown) contact AA Electric.

Stud Size	Wire Size — AWG			
	26-22	22-18	16-14	12-10
<b>KYNAR+ INS. (For temp. up to 150°C) —INS.GRIP SLEEVE</b>				
#4		PK18-4R-C	PK14-4R-C	PK10-6R-L
#6		PK18-6R-C	PK14-6R-C	
#8		PK18-8R-C	PK14-8R-C	PK10-8R-L
#10		PK18-10R-C	PK14-10R-C	PK10-10R-L
1/4"		PK18-14R-C	PK14-14R-C	PK10-14R-L
5/16"		PK18-56R-C	PK14-56R-C	PK10-56R-L
3/8"		PK18-38R-C	PK14-38R-C	PK10-38R-L
<b>NON-INSULATED</b>				
#2	P22-2R-C	P18-4R-C	P14-4R-C	
#4	P22-4R-C	P18-6R-C	P14-6R-C	P10-6R-L
#6	P22-6R-C	P18-8R-C	P14-8R-C	P10-8R-L
#8	P22-8R-C	P18-10R-C	P14-10R-C	P10-10R-L
#10	P22-10R-C	P18-14R-C	P14-14R-C	P10-14R-L
1/4"		P18-56R-C	P14-56R-C	P10-56R-L
5/16"		P18-38R-C	P14-38R-C	P10-38R-L
3/8"				
<b>NON-INSULATED MULTIPLE STUD SIZE</b>				
#6, #8, #10		P18-610R-C	P14-610R-C	P10-610R-L
<b>NON-INSULATED HIGH TEMP. (650°F, 343°C max.)</b>				
#6		P18-6RHT6-C	P14-6RHT6-C	P10-6RHT6-L
#8		P18-8RHT6-C	P14-8RHT6-C	P10-8RHT6-L
#10		P18-10RHT6-C	P14-10RHT6-C	P10-10RHT6-L
1/4"				P10-14RHT6-L

Stud Size	Wire Range: 16 - 12 AWG		
	Nylon Ins.	Vinyl Ins.	Non-Ins.
	Std. & Exp. Ins.	Std. & Exp. Ins.	
<b>HEAVY DUTY</b>			
#6	PN12-6HDR-L	PV12-6HDR-L	P12-6HDR-L
	PN12-6HDRX-L	PV12-6HDRX-L	
#8	PN12-8HDR-L	PV12-8HDR-L	P12-8HDR-L
	PN12-8HDRX-L	PV12-8HDRX-L	
#10	PN12-10HDR-L	PV12-10HDR-L	P12-10HDR-L
	PN12-10HDRX-L	PV12-10HDRX-L	
1/4"	PN12-14HDR-L	PV12-14HDR-L	P12-14HDR-L
	PN12-14HDRX-L	PV12-14HDRX-L	
5/16"	PN12-56HDR-L	PV12-56HDR-L	P12-56HDR-L
	PN12-56HDRX-L	PV12-56HDRX-L	
3/8"	PN12-38HDR-L	PV12-38HDR-L	P12-38HDR-L
	PN12-38HDRX-L	PV12-38HDRX-L	

Stud Size	Wire Size — AWG			
	8	6	4	2
<b>LARGE GAUGE VINYL INS. — STD. AND EXP. INS.</b>				
#8	PV8-8R-Q	PV6-8R-E		
	PV8-8RX-Q	PV6-8RX-E		
#10	PV8-10R-Q	PV6-10R-E	PV4-10R-E	PV2-10R-X
	PV8-10RX-Q	PV6-10RX-E	PV4-10RX-E	PV2-10RX-X
1/4"	PV8-14R-Q	PV6-14R-E	PV4-14R-E	PV2-14R-X
	PV8-14RX-Q	PV6-14RX-E	PV4-14RX-E	PV2-14RX-X
5/16"	PV8-56R-Q	PV6-56R-E	PV4-56R-E	PV2-56R-X
	PV8-56RX-Q	PV6-56RX-E	PV4-56RX-E	PV2-56RX-X
3/8"	PV8-38R-Q	PV6-38R-E	PV4-38R-E	PV2-38R-X
	PV8-38RX-Q	PV6-38RX-E	PV4-38RX-E	PV2-38RX-X
1/2"	PV8-12R-Q	PV6-12R-E	PV4-12R-E	PV2-12R-X
	PV8-12RX-Q	PV6-12RX-E	PV4-12RX-E	PV2-12RX-X

Stud Size	Wire Size — AWG			
	8	6	4	2
<b>NON-INSULATED</b>				
#8	P8-8R-Q	P6-8R-E		
#10	P8-10R-Q	P6-10R-E	P4-10R-E	P2-10R-X
1/4"	P8-14R-Q	P6-14R-E	P4-14R-E	P2-14R-X
5/16"	P8-56R-Q	P6-56R-E	P4-56R-E	P2-56R-X
3/8"	P8-38R-Q	P6-38R-E	P4-38R-E	P2-38R-X
1/2"	P8-12R-Q	P6-12R-E	P4-12R-E	P2-12R-X

\*For heavy duty sizes #8, #6, #4 AWG use HDR, ie: P8-8HDR-Q