



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

| | |
|--|--|
| Material | High Conductivity Seamless Copper Tube |
| Plating | Electro-Tin |
| Wire Size & Type | Stranded Copper Flex Cable; 4 AWG (105/24) Diesel Locomotive, 4 AWG FLEX K,M Class K & Class M |
| Wire Strip Length | 7/8 in. |
| Stud Size | 1/4 in. |
| UL Listed Wire Connector | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. |
| UL Temperature Rating | 90 ° C |
| C.S.A Certified Wire Connector | Yes |
| Panduit Color Code on Barrel | GRAY |
| Panduit Die Index No. on Barrel | P29 |
| Alternate Industry Die Index No. () on Barrel | (8) |



| | | | | | |
|-----|------|-----|-----|--|-----------------------|
| | | | | PANDUIT CORP. TINLEY PARK, ILLINOIS | |
| | | | | LCAF4-14-L Copper Lug - One-Hole, Flared Barrel | |
| 00 | 9/02 | SAB | DRL | RELEASED | 10321 |
| REV | DATE | BY | CHK | DESCRIPTION | ECN |
| | | | | | SCALE N/A |
| | | | | | DRAWING NO / CAD FILE |
| | | | | | LCAF4-14-CUST |