

PIDG Ring Tongue Terminals

Material and Finish

Insulation Nylon
 Terminal Body and Metallic Sleeve — Copper per ASTM B-152, tin plated per MIL-T-10727

Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Stud Size	Dim. W	Terminal Insulation Color	Wire Insulation Diameter Max.	Part Numbers Loose Piece
26-22 202-810 [0.10-0.41]	0.51 .020	2	3.56	Yellow	2.08 .082	323912*
		M2	.140			
		4	5.16			
		M3.5	.203			
		6	5.16			
22-16 509-3,260 [0.26-1.65]	0.84 .033	8	6.35	Yellow	2.08 .082	323916*
		M4	.250			
		10	6.35			
		M3.5	.281			
		6	7.14			
		M4	.312			
		8	7.92			
		M4	.312			
		10	7.92			
		M6	.469			
16-14 2,050-5,180 [1.04-2.62]	0.84 .033	5/16	11.91	Red	3.56 .140	31880*
		M8	.469			
		3/8	13.49			
		M8	.531			
		4	6.35			
		M4	.343			
		6	6.35			
		M4	.343			
		8	8.71			
		M4	.343			
16-14D ¹ 2,050-5,180 [1.04-2.62]	1.27 .050	8	8.71	Blue	4.32 1.70	328996*
		M4	.343			
		10	8.71			
		M4	.343			
		10	8.71			



*Available in small packaging quantities.
¹Heavy duty for extra mechanical strength.