

Search Results

Evaluate

- FAQ's
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'LCAX2-10-E'

Your search criteria matched only one product, shown below

LCAX2-10-E



For Use with Flexible, Extra-Flexible, and Code Stranded Copper Conductors

- Can be used with code conductor and flex conductor class: G, H, I, K, M and Diesel Locomotive
- Generously beveled wire entry prevents bent back strands when inserting conductor into barrel
- Color-coded barrels marked with *PANDUIT* and specified competitor die index numbers for proper crimp die selection
- Inspection window to visually assure full conductor insertion
- Tin-plated to inhibit corrosion
- UL Listed and CSA Certified to 35 KV** and temperature rated to 90°C when crimped with *PANDUIT* and specified competitor crimping tools and dies
- American Bureau of Shipping Approved

Note: These flex conductor lugs are manufactured for use with AWG wire only.

Part Number	LCAX2-10-E
RoHS Compliancy Status	Compliant
Part Description	Flex Lug, #2 AWG, #10 Stud Hole
Length (In.)	1.40
Length (mm)	35.6
Class G,H, I, K, M	#2 AWG
Diesel Locomotive	#2 AWG
Stud Hole Size (In.)	#10
Tongue Width (In.)	.70
Barrel Length (In.)	.59
Angle	Straight
Barrel Length (mm)	15.0
CE Compliant	No
CE Marking	No
Panduit Color Code	Brown
Panduit Die Index No.	P33
Pricing Description	Copper Compression Lug, 1 Hole, #2 AWG Flex, #10 (M5) Stud
Stud Hole Size (mm)	M4
Tongue Thickness	.11
Tongue Type	Standard
Tongue Width (mm)	17.8
Wire Range (mm ²)	35
Wire Strip Length (In.)	11/16
Wire Strip Length (mm)	17.0
Min. Order UOM	PC
Min. Order Qty.	1
Burndy Die Index No.	10
T&B Die Index No.	33
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	<input type="button" value="e"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.