



MH18-6R/L
Stud Size: 6
Wire Range: 22-18



MH18-8R/L
Stud Size: 8
Wire Range: 22-18




MH18-10R/L
Stud Size: 10
Wire Range: 22-18

Stud Size
Wire Range


Ring Tongues - Heat Shrink Brazed Seam 16-14 AWG




Product Number [†]	UPC (054007-)	Wire Range (AWG)	Stud Size	W	C	L	E	Thickness	Barrel Length	Barrel I.D.	Terminals per Bag	Terminals per Case
MH14-6R/LX	06320	16-14	6	0.31	0.15	1.00	0.84	0.030	0.25	0.090	25	100
MH14-6R/LK	06321	16-14	6	0.31	0.15	1.00	0.84	0.030	0.25	0.090	—	250
MH14-8R/LX	06324	16-14	8	0.31	0.18	1.00	0.84	0.030	0.25	0.090	25	100
MH14-8R/LK	06325	16-14	8	0.31	0.18	1.00	0.84	0.030	0.25	0.090	—	250
MH14-10R/LX	06326	16-14	10	0.31	0.20	1.00	0.84	0.030	0.25	0.090	25	100
MH14-10R/LK	06327	16-14	10	0.31	0.20	1.00	0.84	0.030	0.25	0.090	—	250
MH14-14R/SX	06330	16-14	1/4	0.47	0.26	1.1	0.86	0.030	0.25	0.090	25	100
MH14-14R/SK	06331	16-14	1/4	0.47	0.26	1.1	0.86	0.030	0.25	0.090	—	250
MH14-516R/SX	06336	16-14	5/16	0.47	0.33	1.1	0.86	0.030	0.25	0.090	25	100
MH14-516R/SK	06337	16-14	5/16	0.47	0.33	1.1	0.86	0.030	0.25	0.090	—	250
MH14-38RX	06334	16-14	3/8	0.56	0.28	1.1	0.87	0.030	0.25	0.090	25	100
MH14-38RK	06335	16-14	3/8	0.56	0.28	1.1	0.87	0.030	0.25	0.090	—	250




MH14-6R/L




MH14-8R/L




MH14-10R/L



MH14-14R/S



MH14-516R/S



MH14-38R

Stud Size
Wire Range

6
16-14

8
16-14

10
16-14

1/4
16-14

5/16
16-14

3/8
16-14

[†]Product Number ending in X = box; Product Number ending with K = bulk