Material		High Conductivity Seamless Copper Tube			
Plating		Electro-Tin		(m) <u>u</u>	
Wire Size		2/0 AWG			
Wire Type		Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	L AR		
Wire Strip Length		1-9/16 in.			
Stud Size		1/4 in.	.35±.04	.75±.02 - (2) PLS	
UL Listed Wire Connector		Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	- 	• 1.53±.04 • • • • • • • • • • • • • • • • • • •	
UL Temperature Rating		90° C			
C.S.A Certified Wire Connector		Yes	.13±.01		
Panduit Color Code on Barrel		BLACK			
Panduit Die Index No. on Barrel		. P45			
Alternate Industry Die Index No. () on Barrel		(13)		1.50±.04	
	CERTIFIE	ED LISTED Wire Connector		.45±.01 Color coded barrel markings	
				2.34 REFBeveled wire entry	
				CORP. TINLEY PARK, ILLINOI	
				LCC2/0-14BF-X Copper Lug - Two-Hole, Long Barrel, 90° Angle Tongue	
0 9/02 SAB DRL RELEASED					
EV DATE	ВҮ СНК	DESCRIP	TION	ECN SCALE N/A DRAWING NO / CAD FILE LCC2_0-14BF-CUST	

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.