

# **Network and Electrical Solutions**

UNIFIED PHYSICAL INFRASTRUCTURESM



-Search-

Entire Site

### Evaluate

- FAQ's

- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

## Home > Products Overview > Search Results >

Current refinements (click 

to remove) Search Tips

☑ Text Search: 'PNF14-5SLF-M'

Your search criteria matched only one product, shown below

# PNF14-5SLF-M



- Locks in place for a secure connection in limited spaces
- Fork design provides for fast and easy installation, without the need to remove fastener
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V -2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486

Part Number	PNF145SLF-M
RoHS Compliancy Status	Compliant
Part Description	Short Locking Fork Terminal, 16- 14 AWG, #5 stud size, funnel entry, nylon insulated.
CSA Certified	Yes
UL Listed	Yes
• Length (In.)	.75
• Length (mm)	19.1
• Width (In.)	.25
• Width (mm)	6.4
Bolt Dia.	.65
CE Compliant	No
CE Marking	No
Clearance	.19
Clearance (mm)	4.8
• Max. Ins.	.162
Panduit Color Code	Blue
Pricing Description	Short Locking Fork Terminal, nylon insulated, 16 14 AWG, #5 stud size, funnel entry
Stock	.03
• Stock (mm)	0.8
Stud Size	#5
■ Tool	CT-1550, CT-1551, CT-2500
Wire Range	16 – 14 AWG
● Wire Range (mr²l)	1.0 – 2.5
Min. Order UOM	PC
Min. Order Qty.	1000
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	ė

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Home | Industries | Solutions | Products | Partners | Support | Contact Us | Site Map | Careers Copyright © 1995-2009, PANDUIT CORP. All rights reserved. Legal Information | Privacy Policy