

Ring Terminals

Selection Information



**PIDG Nylon Insulated with Insulation Grip**

- Copper inner sleeve
- Vibration resistant
- Barrel serrations
- Nylon insulation



**PLASTI-GRIP Vinyl Insulated**

- Funnel ramp entry
- Barrel serrations or dimples
- Vinyl insulation



**SOLISTRAND Uninsulated**

- Bell mouth
- Brazed seam
- Barrel serrations or dimples

Wire Size	Stud Size	PIDG Nylon Insulated	PLASTI-GRIP Vinyl Insulated	SOLISTRAND Uninsulated
22-16	6	53407-1	34142	34107
	8	53408-1	34145	34108
	10	36154	34146	34112
16-14	6	320619	34158	321684
	8	320565	34160	324955
	10	36160	34161	34123
12-10	8	53424-1	34853	32994
	10	36161	34854	33457
	1/4 [6.35]	320569	34855	35772
8	10	—	52263-1	33460
	1/4 [6.35]	—	52041-3	33461
	5/16 [7.94]	—	52291	33462
	3/8 [9.53]	—	52291-1	33463
	1/2 [12.70]	—	52262-1	35664
6	10	—	52265	33464
	1/4 [6.35]	—	52042-3	—
	5/16 [7.94]	—	52264-2	33466
	3/8 [9.53]	—	52264-1	33467
	1/2 [12.70]	—	52350	320344
4	10	—	52043-2	33468
	1/4 [6.35]	—	52043-3	33469
	5/16 [7.94]	—	52266-3	33470
	3/8 [9.53]	—	52266-4	33471
	1/2 [12.70]	—	—	35668
2	1/4 [6.35]	—	52267-1	52267
	5/16 [7.94]	—	52044-4	322870
	3/8 [9.53]	—	52044-5	321600
	1/2 [12.70]	—	—	35185
1/0	3/8 [9.53]	—	—	36917
	1/2 [12.70]	—	—	36919
2/0	3/8 [9.53]	—	—	321871
	1/2 [12.70]	—	—	321873
3/0	3/8 [9.53]	—	—	321875
4/0	3/8 [9.53]	—	—	321878
	1/2 [12.70]	—	—	321880