TDS # 25123

Division of ITW Chemtronics ®

1.25 mm Fiber Optic Sleeve Cleaning SwabPolyester Fiber Tip

PRODUCT DESCRIPTION

The 1.25 mm Fiber Optic Sleeve Cleaning Swab (patent pending) is ideally suited for cleaning contamination from 1.25 mm fiber optic sleeves and polishing pucks. The 1.25 mm diameter polyester tip fits tightly and conforms to the inside of all 1.25 mm mating sleeves, adapters and slurry polishing fixtures. Critical surfaces are cleaned of all contamination. This swab may be used wet or dry to remove dirt and oil contamination. Solvent cleaners such as Electro-Wash® PX or Electro-Wash® CZ cleaner degreasers are 100% compatible with this swab. No adhesives are used in our proprietary manufacturing process, thereby minimizing leachable contaminants. The swab head contains no seams or hard surface that could scratch critical surfaces.

Patent Pending.

This product is not designed or intended for cleaning the optical surface of connectors.

TYPICAL APPLICATIONS

Cleaning of fiber optic sleeves 1.25 mm in size.

Removal of slurry from 1.25 mm ferrule polishing fixtures.

COMPATIBILITY

Coventry's Fiber Optic Sleeve Cleaning Swab is compatible with Electro-Wash® PX and Electro-Wash® CZ cleaner degreasers, isopropyl alcohol and acetone.

AVAILABILITY

25123X 1.25 mm head diameter, 17 mm head length

Polypropylene handle

Overall swab length 6 inches 100 / bag, 5 bags per box.

25125F 1.25 mm head diameter, 17 mm head length

Polypropylene handle

Overall swab length 6 inches

15/Tube

MANUFACTURED BY:

 $COVENTRY^{TM} \ Clean \ Room \ Products$

Division of ITW Chemtronics®

8125 Cobb Center Drive

KENNESAW, GA 30152 REV. D 05/04

Electro-Wash® and Chemtronics® are registered trademarks of ITW Chemtronics. All rights reserved. CoventryTM, is a trademark of ITW Chemtronics. All rights reserved.

TECHNICAL HOT LINE 1-800-TECH-401