



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS

DOC. NO. SPC-F005 \* Effective: 7/8/02 \* DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1172	B	UPDATED TO TABULAR SPEC	HYO	5/8/01	JC	5/8/01	JC	5/8/01
1884	C	Update To RoHS Compliant	EO	1/25/06	HO	1/25/06	HO	1/25/06



SPC Type No.	Spool Length (Feet)	Width (Inches)	Spool Color
1606	5	0.025	Silver
1607		0.050	Gold
1608		0.075	Green
1609		0.100	Blue
1610		0.125	Brown
1611	25	0.025	Silver
1612		0.050	Gold
1613		0.075	Green
1614		0.100	Blue
1615		0.125	Brown
1616	100	0.025	Silver
1617		0.050	Gold
1618		0.075	Green
3325		0.100	Blue
1620		0.125	Brown



**SPECIFICATIONS:**

- Cleaner, Faster, More Consistent
- Oxide-free clean copper
- More strands of copper (more surface area) per square inch
- Designed to leave a residue which is environmentally safe
- Uses pure type 'R' resin flux conforming to all the requirements of Mil-F-14256F, Type 'R' and ANSI/J-STD-004
- Cleaned and manufactured utilizing the latest technology in environmentally friendly chemicals and processes

DISCLAIMER:  
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:  
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
HISHAM ODISH	11/9/99
CHECKED BY:	DATE:
JOHN COLE	1/25/00
APPROVED BY:	DATE:
DANIEL CAREY	2/7/00

DRAWING TITLE: <b>RoHS COMPLIANT DESOLDERING BRAID</b>			
SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	TA-329	TA-329.DWG	C
SCALE: NTS	U.O.M.: INCHES	SHEET: 1 OF 1	