

ECG® WIRELESS INSPECTION CAMERAS

WIC-1™ With Removable **Color LCD Monitor!** WIC-100™ **DELUXE EDITION** Includes 3.5" color LCD monitor, **Applications:** 9mm camera head and records to HVAC Inspection removable 2GB SD card Automotive Inspection Cable Routing Electrical General Contracting Home Theater Installation Plumbing Inspection Much more!



ECG® WIRELESS INSPECTION CAMERAS The ECG Wireless Inspection Cameras allow for easy visual

The ECG Wireless Inspection Cameras allow for easy visual inspections in hard-to-reach areas, even in total darkness with super bright LEDs! Lightweight, handheld design helps you easily find, diagnose, and solve problems.



WIC-1™: INSPECTION CAMERA

2.4" removable color LCD monitorWaterproof camera and shaft (IP67)

- · Video out for recording
- Includes mirror, hook, and magnet tips
- Includes magnetic monitor base
- One year warranty
- FCC compliant

ECG[®]



WIC-1[™] SPECIFICATIONS

CAMERA	
Imaging Sensor:	CMOS
Total Pixels:	712 x 486
Horizontal View Angle:	50°
Transmission Frequency:	2468 MHz
Modulation Type:	FM
Bandwidth:	18 MHz
Power Supply:	4 x AA Batteries
Weight (With Shaft):	1.17 lbs.
Operating Temperature:	14°F ~ 122°F
Operating Humidity:	15 ~ 85% RH
Diameter (mm/inches)	15.9 / 0.63

MONITOR

Screen Type: 2.36" LCD **Effective Pixels:** 480 x 240 Video System: **NTSC Transmission Frequency:** 2468 MHz **Exterior Supply Voltage:** 8VDC Consumption Current (Max.): 450 mA 0.9 - 1.3V P-P @ 75 ohm **Video Output Level: Dimensions (W x D x H) (inches):** 3.94 x 2.76 x 1.18 Weight: 0.31 lbs. **Operating Temperature:** 14°F ~ 122°F **Operating Humidity:** 15 ~ 85% RH **Power Supply:** Rechargeable Lithium-ion Battery







Removable Color LCD Monitor

ECG Wireless Inspection
Cameras stand apart from the
rest... literally... because they
feature a removable color LCD
monitor that displays crystal
clear video images for accurate
visual inspection. This unique
wireless feature allows you to
put the camera where you need
it... and the monitor where you
can see it... up to 30 ft. away
- affording you a whole new level
of convenience.





WIC-100™ SPECIFICATIONS

1					
	CAMERA		MONITOR		
П	Imaging Sensor:	CMOS	Screen Type:	3.5" TFT-LCD	
	Total Pixels:	640 x 480	Effective Pixels:	320 (RGB) x 240	
П	Horizontal View Angle:	45°	Video System:	PAL/NTSC	
Г	Transmission Frequency:	2468 MHz	Transmission Frequency:	2468 MHz	
П	Modulation Type:	FM	Exterior Supply Voltage:	5 VDC	
	Bandwidth:	18 MHz	Consumption Current (Max.):	500 mA	
			Video Output Level:	0.9 - 1.3V P-P @ 75 ohm	
П	Power Supply:	4 x AA Batteries	Dimensions (W x D x H) (inches):	4 x 2.7 x 1	
	Weight (With Shaft):	1.17 lbs.	Weight:	0.31 lbs.	
П	Operating Temperature:	14°F ~ 122°F	Operating Temperature:	14°F ~ 122°F	
	Operating Humidity:	15 ~ 85% RH	Operating Humidity:	15 ~ 85% RH	
П	Diameter (mm/inches)	9/0.35	Power Supply:	Rechargeable Lithium-ion Battery	







ECG[®] WIRELESS

INSPECTION CAMERA ACCESSORIES





For other accessories and replacement parts, visit www.WirelessInspectionCamera.com



NTE Electronics, Inc. 44 Farrand Street Bloomfield, NJ 07003 www.nteinc.com

Distributed by:		



EL75-02 02/10