

16

16 Coax-Stripping Tool

16 60 100 SB



- ▶ for dismantling and stripping all common Coax-cables between 4.8 - 7.5 mm dia. (e. g. for TV- and satellite antenna), also suitable for PVC round cable 3 x 0.75 mm²
- ▶ with linear scale 5.0 - 20.0 mm
- ▶ double shell, folding back stripping tool
- ▶ with opening spring and locking device
- ▶ tool body made of fibreglass reinforced polyamide

Article-No.	EAN-	Stripping capacities			Δ
Length	Code				
mm	4003773-	ø mm	ø Inch	g	
16 60 100 SB	040811	4.8 - 7.5	5/32 - 19/64	35	
		round cables 3 x 0.75 mm ²			



Dismantling a Coax-cable
4.8 - 7.5 mm Ø



Stripping the conductor of a Coax-cable



Stripping of UTP/STP data cables
between 5.0 - 15.0 mm dia.

16

16 Stripping Tool for Data Cable

16 65 125 SB




- ▶ for dismantling UTP + STP data cable between 5.0 and 15.0 mm dia.
- ▶ double shell, folding back stripping tool
- ▶ with opening spring and locking device
- ▶ practical clip for safe transport and fastening to the working clothes
- ▶ tool body made of fibreglass reinforced polyamide

Article-No.	EAN-	Stripping capacities			Δ
Length	Code				
mm	4003773-	ø mm	ø Inch	g	
16 65 125 SB	043157	5.0 - 15.0 UTP + STP	13/64 - 19/32	65	

16

16 Universal Stripping Tools

16 80 125 SB



16 85 125 SB

- ▶ for dismantling and stripping all common round and damp-proof installation cables between 8.0 - 13.0 mm dia. (e. g. 3 x 1.5 mm² up to 5 x 2.5 mm²)
- ▶ also for use in conduit and distribution boxes
- ▶ double shell, folding back stripping tool
- ▶ with opening spring and locking lever
- ▶ practical clip for safe transport and fastening to working clothes
- ▶ tool body made of fibreglass reinforced polyamide

Model 16 85 125 SB:

- ▶ with additional blade for longitudinal cuts
- ▶ telescopic blade inside
- ▶ stripping device for cross-sections 0.2 - 0.3 - 0.8 - 1.5 - 2.5 - 4.0 mm²

Article-No.	EAN-	Stripping capacities				Δ
Length	Code					
mm	4003773-	Ø mm	Ø Inch	mm ²	g	
16 80 125 SB	040828	round cables 8.0 - 13.0	5/16 - 33/64		65	
		(3 x 1.5 mm ²)				
16 85 125 SB	060444	up to 5 x 2.5 mm ²)		0.2/0.3/0.8/1.5/2.5/4.0	65	



Stripping of round cables between
8.0 - 13.0 mm dia.