

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS			DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1925	Α	RELEASED	EO	8/30/06	JWM	9/1/06	но	9/1/06

Variable Temperature

West Gun

West Gun





Variable temperature heat gun featuring 2 airflow settings with heat and selectable cool air stage for maximum user control. This model also has a soft grip handle for comfortable operation.

- Variable Temperature: Up to 1050°F
- 3 Stage Airflow: Cool Air, 140°F, Low Speed, High Speed
- Safety: Double insulated for safe operation
- Cord: 6½ Ft heavy duty industrial grade rubber Output: 1400 watts
- Voltage: 120 VAC / 60 HZ
- Air Pressure: 1079 pa / 0.157 psi
- CFM: 8½ up to 14.8 Cubic Feet Per Minute
- Circuitry: State-of-the-art interconnect block circuitry
- Switch: Fully enclosed slide switch
- Element Construction: Reinforced mica composite with ceramic disk
- Element Life: 500 hours+
- Weight: 1.25 lb
- Ergonomic handle with comfortable soft grip
- Impact Resistant Housing: Made of high grade, self-extinguishing Valox for added safety
   Dimension: 3.5" Depth 12.5" Width 9.75" Height

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED
HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE
BELIEVE TO BE ACCURATE AND RELIABLE. SINCE
CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE
USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT
FOR THE INTENDED USE AND ASSUME ALL RISK AND
LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY: DATE: 8/30/06 EKLAS ODISH CHECKED BY: DATE: JEFF MCVICKER 9/1/06 APPROVED BY: DATE: 9/1/06 HISHAM ODISH

DRAWING TITLE: Variable Temperature Heat Gun DWG. NO. ELECTRONIC FILE SIZE REV SPC20538 02M6855.DWG Α U.O.M.: INCHES [mm] SCALE: NTS SHEET: 1 OF 1