



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS

DOC. NO. SPC-F005 • Effective: 7/8/02 • DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1925	A	RELEASED	EO	8/30/06	JWM	9/7/06	HO	9/7/06



This model features a dual temperature switch and is designed for general intermittent use.

- Dual Temperature: Low: 600°F High: 950°F
- Safety: Double insulated for safe operation
- Cord: 6½ ft heavy duty industrial grade rubber
- Output: 1300 watts
- Voltage: 120 VAC / 60 HZ
- Air Pressure: 902 pa / 0.132 psi
- CFM: 14.8 Cubic Feet Per Minute
- Circuitry: State-of-the-art interconnect block circuitry
- Switch: Fully enclosed slide switch
- Element Construction: Reinforced mica composite with ceramic disk
- Element Life: 300 hours+
- Weight: 1.25 lb
- Impact Resistant Housing: Made of high grade, self-extinguishing Valox for added safety
- Dimension: 3.5" Depth 12.5" Width 9.75" Height

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
EKLAS ODISH	8/30/06
CHECKED BY:	DATE:
JEFF MCVICKER	9/7/06
APPROVED BY:	DATE:
HISHAM ODISH	9/7/06

DRAWING TITLE: Dual Temperature Heat Gun			
SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	SPC20539	02M6856.DWG	A
SCALE: NTS	U.O.M.: INCHES [mm]	SHEET: 1 OF 1	