




# Intel® PRO/1000 MT Dual Port Server Adapter

**Two Gigabit Copper Server Connections in a Single PCI Slot**

## The Intelligent Way to Connect

Conserve valuable PCI slot space in servers, eliminate server bottlenecks and migrate existing Category-5 networks to Gigabit Ethernet easily and cost-effectively with the Intel® PRO/1000 MT Dual Port Server Adapter. Featuring flexible, auto-negotiating 10/100/1000 Mbps performance, the Intel PRO/1000 MT Dual Port Server Adapter is designed to automatically scale with growing networks.



Enhance server performance further by teaming the two connections together or team with other Intel® PRO Server Adapters using Intel's advanced server feature software to achieve multi-Gigabit scalability and redundant failover capability. A compact form factor and swappable low-profile bracket allow this dual port Gigabit adapter to fit in even high-density, rack-mounted 1U and 2U servers. With a flexible design that fits almost any type of PCI bus, the standards-based management features and wide network operating system support help to ensure extensive compatibility with the latest server and networking environments.

- Easy, cost-effective 10/100/1000 migration over existing CAT-5 cabling
- Multi-Gigabit scalability and increased uptime through advanced server features
- Optional low-profile bracket included for high-density, rack-mounted servers

**Intel® PRO**  
Network Connections

Features	Benefits
<b>WIDESPREAD COMPATIBILITY</b>	
<b>Support for most NOSs</b>	Enables widespread deployment
<b>Intel® SingleDriver™ technology</b>	Common driver suite for Gigabit Ethernet reduces installation complexity
<b>Backward Compatibility with previous generations of Intel PRO/1000 Network Adapters</b>	Reduces support costs and simplifies installation and maintenance
<b>Supports 64- or 32-bit PCI-X 1.0 or PCI 2.2 buses</b>	This flexible, auto-sensing adapter works in a variety of bus types
<b>Remote Management Support (WfM, RIS, SNMP/DMI)</b>	Reduces support costs with remote management based on industry-wide standards
<b>IEEE 802.3ab Compatibility</b>	Supports Gigabit Ethernet industry-wide networking standard
<b>NEW FEATURES IN THE INTEL PRO/1000 MT DUAL PORT SERVER ADAPTER</b>	
<b>Intel® 82546 Gigabit Controller</b>	Enables two Gigabit connections in a single adapter, delivering increased bandwidth for slot-constrained servers and providing high performance, reliability, and low power use in a single, integrated, dual port Gigabit Ethernet controller chip
<b>Full-height and low-profile, screw-on brackets included with each adapter</b>	Compatible with full-height and low-profile PCI slots—the standard, full-height bracket can be easily swapped out and replaced by the shorter, low-profile bracket, for installation in high-density 1U and 2U servers that feature low-profile PCI slots
<b>Interrupt Moderation</b>	Delivers increased performance while significantly reducing CPU utilization
<b>Advanced Cable Diagnostics</b>	Dynamically tests and reports network problems (interrupts, error rate, cable length) and automatically compensates for cable issues (cross over cable, wrong pin-out/polarity)
<b>Large Send Off-load/TCP Segmentation Off-load</b>	Compatible with Large Send Off-load feature of Microsoft Windows® Server 2003, 2000 and XP which enables wire speed performance with low CPU utilization
<b>Expanded Advanced Server Features</b>	Intel® ANS software increases uptime with redundant, teamed connections and scales bandwidth by balancing network traffic across multiple server connections. Now offers Switch Fault Tolerance and Test Switch Configuration to test compatibility and further increase uptime

## GIGABIT-OVER-COPPER ADVANTAGES

<b>Gigabit speeds on Category-5 cable networks</b>	Able to achieve Gigabit speeds on commonly deployed CAT-5 cabling without costly cable replacement
<b>Compatible with Fast Ethernet</b>	Reduces training costs and ramp rollout quickly
<b>Auto-sensing, self-configuring 10/100/1000 Mbps performance</b>	Enables migration to faster networks easily and inexpensively—adapter will automatically sense when the network is able to support a faster speed, and self-configure to save IT staff time, money and server downtime

SPECIFICATIONS		Intel® PRO/1000 MT Dual Port Server Adapter	
<b>GENERAL</b>			
Product Codes	PWLA8492MT		
Connectors	Two RJ-45		
IEEE Standard/Network Topology	10BASE-T, 100BASE-TX, 1000BASE-T		
Wiring	Cat-5, 4-pair		
<b>ADAPTER PRODUCT FEATURES</b>			
Intel® SingleDriver™ technology	■		
Plug and Play Specification Support	Standard		
Easy Installation, Intel® PROSet Utility and Intel® PRO Intelligent Install	■		
Auto-negotiation, Full-duplex Capable	■		
Includes a Low-profile and a Full-height Bracket	■		
Cable Distance	100m		
<b>NETWORK MANAGEMENT</b>			
Wired for Management (WfM) Baseline v2.0 Enabled for Servers	■		
DMI 2.0 Support, WMI & SNMP-manageable	■		
Offline Diagnostics	■		
Dynamic Cable Diagnostics	■		
Intel® Boot Agent	■		
ACPI Power Management	■		
Wake on LAN*	■		
PXE 2.0	■		
<b>NOS SOFTWARE SUPPORT</b>			
Microsoft Windows® Server 2003 and 2000	■		
Microsoft Windows® XP 32- and 64-bit Editions	■		
Microsoft Windows NT® 4.0	■		
Linux® 2.4.x or later (32- and 64-bit)	■		
FreeBSD 4.x or later	■		
Novell Netware® 4.11, 4.2, 5.0, 5.1, 6.0	■		
SunSoft Solaris® 7, 8	■		
UnixWare® 7.x, OpenUNIX 8 (ddi8)	■		
SCO5*	■		
<b>INTEL BACKING</b>			
Limited Lifetime Warranty	■		
90-day Money-back Guarantee (U.S. and Canada)	■		
		<b>ADVANCED SOFTWARE FEATURES</b>	
		Adapter Fault Tolerance	■
		Switch Fault Tolerance	■
		Adaptive Load Balancing	■
		Fast EtherChannel*1	■
		Gigabit EtherChannel*1	■
		IEEE 802.3ad (Link Aggregation Control Protocol)*1	■
		Test Switch Configuration	■
		PCI Hot Plug* and Active PCI*	■
		802.1Q VLANs	■
		802.3x Flow Control	■
		TCP Checksum Offload	■
		IEEE 802.1p	■
		TCP Segmentation/Large Send Off-load	■
		Interrupt Moderation	■
		Save and Restore	■
		<b>TECHNICAL FEATURES</b>	
		Data Rate(s) Supported per Port	10, 100 and 1,000-Mbps
		Bus Type	PCI/PCI-X
		Bus Width	32- or 64-bit
		Bus Speed (MHz)	33/66/100/133
		Onboard Memory	128 KB
		Interrupt Levels	INTA
		IEEE Support	802.3ab
		Hardware Certifications	FCC A, CE
		Data Transfer Mode	Bus-master DMA
		Controller—Processor	Intel® 82546
		Typical Power Consumption	1A at +5VDC
		Operating Temperature	0–55°C
		Operating Humidity	85% at +55°C
		<b>PHYSICAL DIMENSIONS</b>	
		Length	16.5cm (6.6 in)
		Width	6.4cm (2.5 in)
		Height of Full-Height End Bracket	12.1cm (4.75 in)
		Height of Low-Profile End Bracket	8.1cm (3.2 in)

## ORDER CODES

PWLA8492MT (Single Packs)  
PWLA8492MTBLK5 (Five Packs)

## COMPANION PRODUCTS

Consider these Intel® products in your server and network planning:

- Intel® PRO/1000 MT Desktop Adapters
- Intel® PRO/1000 MT Server Adapters
- Intel® PRO/1000 MF Server Adapters
- Intel® PRO/1000 MF Server Adapters (LX)
- Intel® PRO/1000 MF Dual Port Server Adapters
- Intel® PRO/1000 MT Quad Port Server Adapters
- Other Intel® PRO Desktop, Mobile, Wireless and Server Adapters
- Intel® Xeon™ processors
- Intel® Server Boards

## NETWORK-READY PCS

Top PC and server manufacturers offer Intel® adapters in their new products. Specify or ask for Intel® PRO Network Connections with your next PC, server, or mobile PC purchase. For a list of preferred suppliers, visit us on the World Wide Web: [www.intel.com/network/connectivity/how\\_to\\_buy/index.htm](http://www.intel.com/network/connectivity/how_to_buy/index.htm).

## CUSTOMER SUPPORT

Intel® customer Support Services offers a broad selection of programs including phone support and warranty service. For more information, contact us at [support.intel.com/support/network](http://support.intel.com/support/network) Service and availability may vary by country.

## FOR PRODUCT INFORMATION

To speak to a customer service representative regarding Intel® products, please call 1-800-538-3373 (U.S. and Canada) or visit [www.intel.com/support/9089.htm](http://www.intel.com/support/9089.htm) for the telephone number in your area. For additional product information on the Intel® Networking and Communication products, visit [www.intel.com/network/connectivity](http://www.intel.com/network/connectivity).

## ONLINE DOCUMENTS

For the latest product information, visit us on the World Wide Web at [www.intel.com/network/connectivity](http://www.intel.com/network/connectivity)

Information in this document is provided in connection with Intel® products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, life-saving, or life-sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice. For the most current product information, please visit <http://www.intel.com/network/connectivity>

\*Other names and brands may be claimed as the property of others.

\*Available only when used with a capable switch.

Copyright © Intel Corporation 2003.  
All rights reserved.  
1003/LAD/PL/OC/PDF



NP2116.01  
Please recycle