


















# PX-235/ PX-246

## LP PCle 1xRS232 1MBaud

## "SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



### **Features**

- 1 port RS232
- PCI Express x1, x4, x8 & x16 lane slots socket size
- 256 Byte Tx and 256 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

#### **Options**



PX-235: LP PCIe 1xRS232 1MBaud

PX-246: PCIe 1xRS232 1MBaud



\*For 2 port see PX-257 & PX-203 - max

baud rate is driver dependant

#### Description

Low Profile PCI Express Card providing one RS232 serial port. Up to 921,600 data transfer rates and the 256 byte deep transmit and 256 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC.


PCI Express is the latest standard in PC connectivity.

With Brainboxes' industry renowned Lifetime Warranty and Lifetime Support! PX-246 - Standard profile version; PX-235 - Low profile version.

#### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Microsoft Windows 7 32bit & 64bit Editions
- Windows Server 2008 32 bit & 64 bit Editions



Windows Server 2003 32 bit & 64 bit Editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.

























ORDER Description

LP PCIe 1xRS232 1MBaud PCIe 1xRS232 1MBaud

Code

PX-235

PX-246



# LP PCIe 1xRS232 1MBaud

#### PX-235/ PX-246: Full Specification

1 7-255/ 17-240. Tuli Specification		
Port	Ports	1 x RS232
Pin 1 DCD RS232 Pinout (9 pin Male)	Connector	DB9 connector (9 Pin Male)
Pin 2         RXD         1         5           Pin 3         TXD	FIFO size	256 RX FIFO + 256 TX FIFO
Pin 4 DTR Pin 5 GND Pin 6 DCP	Operating Distance	EIA - RS232 Standard
Pin 6 DSR Pin 7 RTS Pin 8 CTS Pin 9 RI 6 9	Cable	No Cable; Integrated Connector
Port Settings	Baud Rate	921,600
921,600	Data Bits	5,6,7 or 8
<b>&gt;&gt;&gt;</b> >>	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	RTS/CTS DSR/DTR XON/XOFF
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Microsoft Windows 7 32bit & 64bit Editions
DCI		Microsoft Windows 7 32bit & 64bit Editions
PCI>>> EXPRESS		Windows Server 2008 32 bit & 64 bit Editions Windows Vista 32 bit & 64 bit Editions
		Windows Server 2003 32 bit & 64 bit Editions
	BUS	PCI Express x1, x4, x8 & x16 lane slots :
Approvals	Other Approvals	WEEE ROHS METL EMC: CE
	Microsoft Approvals	Microsoft Certified Gold Partner
		Microsoft Windows 7 32bit & 64bit Editions Windows Server 2008 32
RoHS college of the c		bit & 64 bit editions
		Windows Vista 32 bit & 64 bit editions Windows Server 2003 32 bit & 64 bit editions
General	PCB Layers	4
	Power Consumption	380mA @ 3.3V
	Weight	0.046 Kg
	Size	130x20x80 mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	LP PCle 1xRS232 1MBaud / PCle 1xRS232 1MBaud
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5 European Electronics Industry Awards	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Datasheet Version: 4.36 Published on: 2009/12/8