
















UC-235/UC-246

LP uPCI 1xRS232

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Description

Low Profile Universal PCI providing one RS232 serial port. Up to 115,200 data transfer rates and the 128 byte deep transmit and 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC.

Universal PCI is fully compatible with both 3.3Volt and 5Volt PCI slots.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Features

- 1 port RS232
- PCI 3.0
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



UC-235: LP uPCI 1xRS232

UC-246 uPCI 1xRS232



Software

Microsoft signed drivers (easy installation & robust operation) for:

- Microsoft Windows 7 32bit & 64bit Editions
- Windows Server 2008 & Windows 2000
- Windows Vista 32 bit and 64 bit editions
- Windows Server 2003 32 bit & 64 bit Editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.

























ORDER Description LP uPCI 1xRS232 uPCI 1xRS232

Code UC-235

UC-246



LP uPCI 1xRS232

UC-235/UC-246: Full Specification

Port	Ports	1 x RS232
Pin 1 DCD RS232 Pinout (9 pin Male)	Connector	DB9 connector (9 Pin Male)
Pin 2 RXD 1 5 Pin 3 TXD 1 5	FIFO size	128 RX FIFO + 128 TX FIFO
Pin 4 DTR Pin 5 GND Pin 6 DSR	Operating Distance	EIA - RS232 Standard
Pin 6 DSR Pin 7 RTS Pin 8 CTS Pin 9 RI 6 9	Cable	No Cable; Integrated Connector
Port Settings	Baud Rate	115,200
115,200	Data Bits	5,6,7 or 8
> > > >	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	RTS/CTS DSR/DTR XON/XOFF
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Microsoft Windows 7 32bit & 64bit Editions
		Microsoft Windows 7 32bit & 64bit Editions
PCI °		Windows Server 2008 32 bit & 64 bit Editions Windows Vista 32 bit & 64 bit Editions
		Windows Server 2003 32 bit & 64 bit Editions
	BUS	PCI 3.0 : Peripheral Component Interface
Approvals	Other Approvals	WEEE IEEC CB Scheme METL FCC Compliant
	Microsoft Approvals	Microsoft Certified Gold Partner
TEGEF TO ALEX		Microsoft Windows 7 32bit & 64bit Editions Windows Server 2008 32
CB SCHEME		bit & 64 bit editions
		Windows Vista 32 bit & 64 bit editions Windows Server 2003 32 bit & 64 bit editions
General	PCB Layers	4
	Power Consumption	190mA @ 5V, 12mA @ 12V
	Weight	0.059 Kg
	Size	125x20x12 mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	LP uPCI 1xRS232 / uPCI 1xRS232
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5 Evopea Electronics Industry Award	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Datasheet Version: 4.36 Published on: 2009/12/8