
















UC-101 LP uPCI 1+1xRS232

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 1+1 port RS232
- PCI 3.0
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



UC-101: LP uPCl 1+1xRS232

Description

Universal PCI providing two low profile RS232 serial ports. Up to 115,200 data transfer rates and the 128 byte deep transmit and 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC.

Universal PCI is fully compatible with both 3.3Volt and 5Volt PCI slots.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Server 2008 & Windows 2000
- Windows Vista 32 bit and 64 bit editions
- Windows Server 2003 32 bit & 64 bit Editions
- Windows XP 32 bit & 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.

























ORDER
Description
LP uPCl 1+1xRS232

Code UC-101

For Standard Profile see UC-475

UC-101



LP uPCI 1+1xRS232

UC-101: Full Specification

Port	Ports	1+1 x RS232
Pin 1 DCD RS232 Pinout (9 pin Male) Pin 2 RXD 1 5	Connector	DB9 connector (9 Pin Male)
Pin 3 TXD Pin 4 DTR	FIFO size	128 RX FIFO + 128 TX FIFO
Pin 5 GND Pin 6 DSR	Operating Distance	EIA - RS232 Standard
Pin 7 RTS Pin 8 CTS	Cable	1 PORT RS232 on fly lead
Pin 9 Ri 6 9		
Port Settings	Baud Rate	115,200
115,200	Data Bits	5,6,7 or 8
> >> >	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	RTS/CTS DSR/DTR XON/XOFF
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Windows Server 2008 32 bit & 64 bit Editions
PCI [°]		Windows Vista 32 bit & 64 bit Editions Windows Server 2003 32 bit & 64 bit Editions
PGI		Windows XP 32 bit & 64 bit Editions
		Microsoft Windows 2000
	BUS	PCI 3.0 : Peripheral Component Interface
Approvals	Other Approvals	WEEE ROHS IEEC CB Scheme METL
	Microsoft Approvals	Microsoft Certified Gold Partner
TECEF		Windows Server 2008 32 bit & 64 bit editions Windows Vista 32 bit & 64 bit editions
RoH5 CB SCHEME		Windows Server 2003 32 bit & 64 bit editions Windows XP 32 bit &
		64 bit editions
General	PCB Layers	4
	Power Consumption	180mA @ 5V, 30mA @ 12V
	Weight	0.058 Kg
	Size	130x20x80 mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	LP uPCI 1+1xRS232 /
		1 PORT RS232 on fly lead
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Floktra OF ***	Made In	Manufactured in the UK by Brainboxes Winner 2005 European
Elektro O5 European Electronics Industry Awards		Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com
made in the Oil		users. Iviore illio. sales@brailiboxes.COM

Datasheet Version: 3.6 Published on: 2009/7/20