













## **RoHS Compliant**



# PX-260/ PX-701

# LP PCle 4xRS232 1MBaud

## "SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



## Features

- 1 port RS232
- PCI Express x1, x4, x8 & x16 lane slots socket size
- 16 Byte Tx and 16 Byte Rx FIFOs
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

### **Options**



PX-260: LP PCIe 4xRS232 1MBaud

PX-701 PCIe 4xRS232 (4x9 pin cable)



#### Description

PCI Express Card providing four RS232 serial ports. Up to 921,600 data transfer rates and the 128 byte deep transmit and 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your laptop/PC.

PCI Express is the latest standard in PC connectivity.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support! PX-701 - Standard profile version; PX-260 - Low profile version.

#### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Server 2008 32 bit & 64 bit Editions
- Windows Vista 32 bit and 64 bit editions
- Windows Server 2003 32 bit & 64 bit Editions
- Windows XP 32 bit & 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.

























ORDER Description LP PCIe 4xRS232 1MBaud PCIe 4xRS232 (4x9 pin cable)

Code PX-260 PX-701

PX-260 PX-701



# LP PCIe 4xRS232 1MBaud

PX-260/ PX-701: Full Specification

PX-260/ PX-701: Full Specification		
Port	Ports	1 x RS232
Pin 1 DCD RS232 Pinout (9 pin Male)	Connector	DB9 connector (9 Pin Male)
Pin 2 RXD 1 5 Pin 3 TXD 1 5	FIFO size	16 RX FIFO + 16 TX FIFO
Pin 4 DTR Pin 5 GND	Operating Distance	EIA - RS232 Standard
Pin 6 DSR Pin 7 RTS Pin 8 CTS Pin 9 RI 6 9	Cable	No Cable; Integrated Connector
Port Settings	Baud Rate	115,200
115,200	Data Bits	5,6,7 or 8
<b>&gt;</b> > > >	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	RTS/CTS DSR/DTR XON/XOFF
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Windows Server 2008 32 bit & 64 bit Editions
PCI >>		Windows Vista 32 bit & 64 bit Editions Windows Server 2003 32 bit & 64 bit Editions
PCI >> express		Windows XP 32 bit & 64 bit Editions
		Microsoft Windows 2000
	BUS	PCI Express x1, x4, x8 & x16 lane slots :
Approvals	Other Approvals	WEEE ROHS METL EMC: CE
_	Microsoft Approvals	Microsoft Certified Gold Partner
MET		Windows Server 2008 32 bit & 64 bit editions Windows Vista 32 bit & 64 bit editions
ROHS		Windows Server 2003 32 bit & 64 bit editions Windows XP 32 bit &
		64 bit editions
General	PCB Layers	4
	Power Consumption	awaiting
	Weight	0.0 Kg
	Size	0x0x0 mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	LP PCIe 4xRS232 1MBaud / PCIe 4xRS232 (4x9 pin cable)
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
THE THE PARTY OF T	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
	0514	A 7111 ( 1 111 OFW
Additional	OEM option	Available for bulk buy OEM
Elektra O5 European Electronics Industry Awards	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year  Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Datasheet Version: 3.51 Published on: 2009/7/6